

Product datasheet

Specifications



aluminium cable connectors,
TransferPacT, for 2 cables 50 to 120
mm², Frame 250A, 3P, set of 3

TPSCON51

Main

Range of product	TransferPacT
Device short name	connectors
Product or component type	Bare cable connector
Accessory / separate part category	Connection accessory
Range compatibility	TransferPacT
Poles description	3P
Quantity per set	Set of 3

Complementary

[In] rated current	250 A
Conductor material	Aluminium
Connections - terminals	Screw terminal2 cable(s) 50...120 mm ² Screw terminal50...120 mm ²
Product compatibility	TA25 TR25

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.000 cm
Package 1 Width	24.500 cm
Package 1 Length	27.000 cm
Package 1 Weight	329.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	10
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	3.660 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant with Exemptions

SCIP Number

6acdf116-a48d-4a7c-a35f-450d712fc277

REACH Regulation

[REACH Declaration](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

End of life manual availability

[End of Life Information](#)

Take-back

No

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins