

Product data sheet

Specifications

SQUARE D



Two Speed Manual Switch - NEMA 1 - 2P - Toggle Operated - Red Indicator - 600VAC

2512KG11B

⚠ Discontinued

Main

Product Duplex Unit Manual Switch

Type K

Complementary

Current Rating 30 A

Cable Entry 0.5" and 0.75" knock-outs (top and bottom)

Horsepower Rating
2 hp 115 V AC
2 hp 230 V AC
3 hp 460 V AC
3 hp 575 V AC
1 hp 90 V DC
2 hp 115 V DC
1.5 hp 230 V DC

Maximum Voltage Rating
600 V AC
230 V DC

Number of Poles 2P

Control Unit Type Toggle

Number of Phases 1 phase

Pilot Light Red indicator, 230 V

Starter Type 2 speed

Electrical Connection Screw clamp terminals

Wire Gauge AWG 14...AWG 10 copper

Height 4.25 in (107.95 mm)

Width 4.5 in (114.3 mm)

Depth 2.75 in (69.85 mm)

Environment

Certifications
UL listed file E42243 CCN NLRV
CSA LR25490 class 3211 05

NEMA Enclosure Rating NEMA 1 painted sheet steel standard size

Ordering and shipping details

Category 21102-2510,2511,2512 K

Discount Schedule CP1

GTIN 00785901505112

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Returnability	No
---------------	----

Country of origin	MX
-------------------	----

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Nbr. of units in pkg.	1
-----------------------	---

Package weight(Lbs)	3.200 oz (90.718 g)
---------------------	---------------------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No