

Data sheet for dv/dt filter plus VPL

Article No. : 6SL3000-2DE41-4AA0



Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data

Output current	1,405 A
----------------	---------

General technical specifications

Power loss	dv/dt reactor	Voltage Peak Limiter (VPL)
at 400 V / 50 Hz	1.111 kW	0.134 kW
at 460 V / 60 Hz	1.154 kW	0.125 kW
at 400 V / 150 Hz	1.230 kW	0.114 kW

Connections

Cable length

for motor, max. (shielded)	300 m (984 ft)
for motor, max. (unshielded)	450 m (1,476 ft)

Design	dv/dt reactor	Voltage Peak Limiter (VPL)
Power cable	2 x hole for M12	-
Load	2 x hole for M12	-
PE conductor	M6 screw	M8 stud
dv/dt reactor	-	1 x hole for M10
DC link	-	1 x hole for M10

Mechanical data

Degree of protection	IP00
----------------------	------

	dv/dt reactor	Voltage Peak Limiter (VPL)
Net weight	158 kg (348 lb)	72 kg (159 lb)

Dimensions

Width	445 mm (17.50 in)	309 mm (12.20 in)
Height	385 mm (15.20 in)	1,313 mm (51.70 in)
Depth	312 mm (12.30 in)	400 mm (15.70 in)

Standards

Compliance with standards	CE, cURus
---------------------------	-----------