# Product datasheet

Specifications



## Circuit breaker frame, ComPacT NS1000L, 150kA/415VAC, 1000A, fixed, electrically operated, without trip unit, 3P

33292

## Main

| | |
|---|---|
| **Range** | ComPacT |
| **Range of product** | ComPacT NS630b...1600 new generation |
| **Device short name** | Compact NS1000L |
| **Product or component type** | Basic frame |
| **Device application** | Distribution |
| **Number of poles** | 3P |
| **[In] rated current** | 1000 A at 50 °C |
| **[Ue] rated operational voltage** | 690 V AC 50/60 Hz |
| **Network type** | AC |
| **Network frequency** | 50/60 Hz |
| **Suitability for isolation** | Yes conforming to EN/IEC 60947-2 |
| **Utilisation category** | Category A |
| **Breaking capacity** | 150 kA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2<br>150 kA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2<br>130 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>100 kA Icu at 500/525 V AC 50/60 Hz conforming to IEC 60947-2 |
| **Breaking capacity code** | L 150 kA 415 V AC |
| **Control type** | Electrically operated |
| **Mounting mode** | Fixed |

## Complementary

| | |
|---|---|
| **[Ui] rated insulation voltage** | 1000 V AC 50/60 Hz conforming to IEC 60947-2 |
| **[Uimp] rated impulse withstand voltage** | 8 kV conforming to IEC 60947-2 |
| **[Ics] rated service breaking capacity** | 150 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 (electrical operation)<br>150 kA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 (electrical operation)<br>130 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 (electrical operation)<br>100 kA at 500/525 V AC 50/60 Hz conforming to IEC 60947-2 (electrical operation) |
| **Mechanical durability** | 10000 cycles conforming to IEC 60947-2 |
| **Electrical durability** | 2000 cycles 690 V AC 50/60 Hz In conforming to IEC 60947-2<br>3000 cycles 440 V AC 50/60 Hz In conforming to IEC 60947-2<br>3000 cycles 690 V AC 50/60 Hz In/2 conforming to IEC 60947-2<br>4000 cycles 440 V AC 50/60 Hz In/2 conforming to IEC 60947-2 |
| **Power losses** | 34 W |
| **Mounting support** | Backplate |
| **Connection pitch** | 70 mm |
| **Protection type** | Without protection |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Height (H)** | 224 mm |
| **Width (W)** | 210 mm |
| **Depth (D)** | 182 mm |

## Environment

| | |
|---|---|
| **Standards** | IEC 60947-2 |
| **Product certifications** | LCIE<br>ASEFA<br>ASTA |
| **Overvoltage category** | III |
| **Electrical shock protection class** | Class II on front face |
| **Pollution degree** | 3 conforming to IEC 60947 |
| **IP degree of protection** | IP40 conforming to IEC 60529 |
| **IK degree of protection** | IK07 conforming to EN 50102 |
| **Ambient air temperature for storage** | -50…85 °C |
| **Ambient air temperature for operation** | -25…70 °C |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Number of Units in Package 1** | 1 |
| **Package 1 Height** | 36.0 cm |
| **Package 1 Width** | 40.0 cm |
| **Package 1 Length** | 23.0 cm |
| **Package 1 Weight** | 13.494 kg |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 18 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Total lifecycle Carbon footprint | **887 kg CO2 eq.** |
| Environmental Disclosure | **Product Environmental Profile** |
| Carbon footprint of the manufacturing phase [A1 to A3] | **189 kg CO2 eq.** |
| Carbon footprint of the distribution phase [A4] | **4 kg CO2 eq.** |
| Carbon footprint of the installation phase [A5] | **2 kg CO2 eq.** |
| Carbon footprint of the use phase [B2, B3, B4, B6] | **673 kg CO2 eq.** |
| Carbon footprint of the end-of-life phase [C1 to C4] | **20 kg CO2 eq.** |

## Use Better

### Materials and Packaging

| | |
|---|---|
| Packaging made with recycled cardboard | **Yes** |
| Packaging without single use plastic | **No** |
| SCIP Number | **21550c2a-6c05-4d3d-8388-9ca38a81a60f** |
| EU RoHS Directive | **Compliant By Exemption** |
| REACh Regulation | **Reference contains Substances of Very High Concern above the threshold** |
| Halogen-free status | **Product contains halogen above thresholds** |
| PVC free | **Yes** |
| Silicone-free | **No** |

## Use Longer

### Lifetime extension

| | |
|---|---|
| Repair | **No** |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Recyclability potential, in % | **56** |
| End of life manual availability | **End of Life Information** |
| Take-back | **No** |
| WEEE Label | **The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins** |