


Product datasheet

Specifications



4 CONN.NG125/LINERGY DX DIST.BLOCK 125A

LVS04047

EAN Code: 3606481867247

Main

Range	Linergy
Range of product	Linergy
Product or component type	Flexible connection
Product name	Linergy DX
product name	PrismaSeT PrismaSeT G enclosure PrismaSeT PrismaSeT P enclosure PrismaSeT PrismaSeT Pack 250 enclosure Linergy Linergy DX distribution block
Accessory / separate part category	Current distribution accessory
Standards	IEC 61439-2, inside enclosure IEC 61439-1, inside enclosure
Product certifications	ASTA

Complementary

Cubicle-device connection	Linergy DX distribution block
installation description	Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm Cubicle - width 650 mm Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Cubicle - width 800 mm Pack enclosure - width 555 mm Pack enclosure - width 600 mm
Installed device	Multi9: fixed NG125 without earth leakage protection - control: toggle Multi9: fixed NG125 with earth leakage protection - control: toggle ComPact: fixed INS40 - control: direct front rotary handle vertical installation ComPact: fixed INS63 - control: direct front rotary handle vertical installation ComPact: fixed INS100 - control: direct front rotary handle vertical installation ComPact: fixed INS125 - control: direct front rotary handle vertical installation ComPact: fixed INS160 - control: direct front rotary handle vertical installation Acti 9: fixed iC120 with earth leakage protection - control: toggle Acti 9: fixed iC120 without earth leakage protection - control: toggle Multi9: fixed NG125 NA - control: toggle ComPact: fixed NG160 NA without earth leakage protection - control: toggle Acti 9: fixed C120 with earth leakage protection - control: toggle Acti 9: fixed C120 without earth leakage protection - control: toggle ComPact: fixed NG160 with earth leakage protection - control: toggle ComPact: fixed NG160 without earth leakage protection - control: toggle ComPact: fixed NSXm without earth leakage protection - control: toggle vertical installation ComPact: fixed NSXm with earth leakage protection - control: toggle vertical installation
Condition of use	Additional connector needed for INS40...160 (to be ordered separately)
[Ie] rated operational current	125 A
Length	240 mm
Net weight	0.52 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

[illegible]

4

Life Is On



17 Feb 2026

600 mm PrismaSeT G floor-standing enclosure Multi9 NG125 without fixed toggle 3P 1 direct 5
600 mm PrismaSeT G wall-mounted enclosure Multi9 NG125 without fixed toggle 3P 1 direct 5
600 mm PrismaSeT G floor-standing enclosure Multi9 NG125 without fixed toggle 4P 1 direct 5
600 mm PrismaSeT G wall-mounted enclosure Multi9 NG125 without fixed toggle 4P 1 direct 5
300 mm PrismaSeT G floor-standing duct Multi9 NG125 without fixed toggle 3P 1 direct 4
300 mm PrismaSeT G wall-mounted duct Multi9 NG125 without fixed toggle 3P 1 direct 4
300 mm PrismaSeT G floor-standing duct Multi9 NG125 without fixed toggle 4P 1 direct 4
300 mm PrismaSeT G wall-mounted duct Multi9 NG125 without fixed toggle 4P 1 direct 4
600 mm PrismaSeT G floor-standing enclosure Multi9 NG125 NA fixed toggle 3P 1 direct 5
600 mm PrismaSeT G wall-mounted enclosure Multi9 NG125 NA fixed toggle 3P 1 direct 5
600 mm PrismaSeT G floor-standing enclosure Multi9 NG125 NA fixed toggle 4P 1 direct 5
600 mm PrismaSeT G wall-mounted enclosure Multi9 NG125 NA fixed toggle 4P 1 direct 5
300 mm PrismaSeT G floor-standing duct Multi9 NG125 NA fixed toggle 3P 1 direct 4
300 mm PrismaSeT G wall-mounted duct Multi9 NG125 NA fixed toggle 3P 1 direct 4
300 mm PrismaSeT G floor-standing duct Multi9 NG125 NA fixed toggle 4P 1 direct 4
300 mm PrismaSeT G wall-mounted duct Multi9 NG125 NA fixed toggle 4P 1 direct 4
600 mm PrismaSeT G floor-standing enclosure ComPact NG160 without fixed toggle 3P 1 direct 5
600 mm PrismaSeT G wall-mounted enclosure ComPact NG160 without fixed toggle 3P 1 direct 5
600 mm PrismaSeT G floor-standing enclosure ComPact NG160 without fixed toggle 4P 1 direct 5
600 mm PrismaSeT G wall-mounted enclosure ComPact NG160 without fixed toggle 4P 1 direct 5
300 mm PrismaSeT G floor-standing duct ComPact NG160 without fixed toggle 3P 1 direct 5
300 mm PrismaSeT G wall-mounted duct ComPact NG160 without fixed toggle 3P 1 direct 5
300 mm PrismaSeT G floor-standing duct ComPact NG160 without fixed toggle 4P 1 direct 5
300 mm PrismaSeT G wall-mounted duct ComPact NG160 without fixed toggle 4P 1 direct 5
600 mm PrismaSeT G floor-standing enclosure ComPact NG160 NA without fixed toggle 3P 1 direct 5
600 mm PrismaSeT G wall-mounted enclosure ComPact NG160 NA without fixed toggle 3P 1 direct 5
600 mm PrismaSeT G floor-standing enclosure ComPact NG160 NA without fixed toggle 4P 1 direct 5
600 mm PrismaSeT G wall-mounted enclosure ComPact NG160 NA without fixed toggle 4P 1 direct 5
300 mm PrismaSeT G floor-standing duct ComPact NG160 NA without fixed toggle 3P 1 direct 5
300 mm PrismaSeT G wall-mounted duct ComPact NG160 NA without fixed toggle 3P 1 direct 5
300 mm PrismaSeT G floor-standing duct ComPact NG160 NA without fixed toggle 4P 1 direct 5
300 mm PrismaSeT G wall-mounted duct ComPact NG160 NA without fixed toggle 4P 1 direct 5
650 mm PrismaSeT P cubicle
800 mm PrismaSeT P cubicle
600 mm PrismaSeT G floor-standing enclosure Acti 9 C120 with fixed toggle 3P 1 direct 5
600 mm PrismaSeT G wall-mounted enclosure Acti 9 C120 with fixed toggle 3P 1 direct 5
600 mm PrismaSeT G floor-standing enclosure Acti 9 C120 with fixed toggle 4P 1 direct 5
600 mm PrismaSeT G wall-mounted enclosure Acti 9 C120 with fixed toggle 4P 1 direct 5
300 mm PrismaSeT G floor-standing duct Acti 9 C120 with fixed toggle 3P 1 direct 4
300 mm PrismaSeT G wall-mounted duct Acti 9 C120 with fixed toggle 3P 1 direct 4
300 mm PrismaSeT G floor-standing duct Acti 9 C120 with fixed toggle 4P 1 direct 4
300 mm PrismaSeT G wall-mounted duct Acti 9 C120 with fixed toggle 4P 1 direct 4
600 mm PrismaSeT G floor-standing enclosure Acti 9 iC120 with fixed toggle 3P 1 direct 5
600 mm PrismaSeT G wall-mounted enclosure Acti 9 iC120 with fixed toggle 3P 1 direct 5
600 mm PrismaSeT G floor-standing enclosure Acti 9 iC120 with fixed toggle 4P 1 direct 5

600 mm PrismaSeT G wall-mounted enclosure Acti 9 iC120 with fixed toggle 4P 1 direct 5

300 mm PrismaSeT G floor-standing duct Acti 9 iC120 with fixed toggle 3P 1 direct 4

300 mm PrismaSeT G wall-mounted duct Acti 9 iC120 with fixed toggle 3P 1 direct 4

300 mm PrismaSeT G floor-standing duct Acti 9 iC120 with fixed toggle 4P 1 direct 4

300 mm PrismaSeT G wall-mounted duct Acti 9 iC120 with fixed toggle 4P 1 direct 4

600 mm PrismaSeT G floor-standing enclosure Multi9 NG125 with fixed toggle 3P 1 direct 5

600 mm PrismaSeT G wall-mounted enclosure Multi9 NG125 with fixed toggle 3P 1 direct 5

600 mm PrismaSeT G floor-standing enclosure Multi9 NG125 with fixed toggle 4P 1 direct 5

600 mm PrismaSeT G wall-mounted enclosure Multi9 NG125 with fixed toggle 4P 1 direct 5

300 mm PrismaSeT G floor-standing duct Multi9 NG125 with fixed toggle 3P 1 direct 4

300 mm PrismaSeT G wall-mounted duct Multi9 NG125 with fixed toggle 3P 1 direct 4

300 mm PrismaSeT G floor-standing duct Multi9 NG125 with fixed toggle 4P 1 direct 4

300 mm PrismaSeT G wall-mounted duct Multi9 NG125 with fixed toggle 4P 1 direct 4

600 mm PrismaSeT G floor-standing enclosure ComPact NG160 with fixed toggle 3P 1 direct 5

600 mm PrismaSeT G wall-mounted enclosure ComPact NG160 with fixed toggle 3P 1 direct 5

600 mm PrismaSeT G floor-standing enclosure ComPact NG160 with fixed toggle 4P 1 direct 5

600 mm PrismaSeT G wall-mounted enclosure ComPact NG160 with fixed toggle 4P 1 direct 5

600 mm PrismaSeT G floor-standing enclosure ComPact NSXm without fixed toggle vertical 3P or 4P 1 connection block 7

600 mm PrismaSeT G wall-mounted enclosure ComPact NSXm without fixed toggle vertical 3P or 4P 1 connection block 7

300 mm PrismaSeT G floor-standing duct ComPact NSXm without fixed toggle vertical 3P or 4P 1 connection block 7

300 mm PrismaSeT G wall-mounted duct ComPact NSXm without fixed toggle vertical 3P or 4P 1 connection block 7

600 mm PrismaSeT G floor-standing enclosure ComPact NSXm with fixed toggle vertical 3P or 4P 1 connection block 7

600 mm PrismaSeT G wall-mounted enclosure ComPact NSXm with fixed toggle vertical 3P or 4P 1 connection block 7

300 mm PrismaSeT G floor-standing duct ComPact NSXm with fixed toggle vertical 3P or 4P 1 connection block 7

300 mm PrismaSeT G wall-mounted duct ComPact NSXm with fixed toggle vertical 3P or 4P 1 connection block 7

600 mm PrismaSeT Pack 250 Pack enclosure Acti 9 C120 without fixed toggle 3P 1 direct 6

600 mm PrismaSeT Pack 250 Pack enclosure Acti 9 C120 without fixed toggle 4P 1 direct 6

600 mm PrismaSeT Pack 250 Pack enclosure Acti 9 iC120 without fixed toggle 3P 1 direct 6

600 mm PrismaSeT Pack 250 Pack enclosure Acti 9 iC120 without fixed toggle 4P 1 direct 6

600 mm PrismaSeT Pack 250 Pack enclosure ComPact INS100 fixed direct front rotary handle vertical 3P 1 direct 6

600 mm PrismaSeT Pack 250 Pack enclosure ComPact INS100 fixed direct front rotary handle vertical 4P 1 direct 6

600 mm PrismaSeT Pack 250 Pack enclosure ComPact INS125 fixed direct front rotary handle vertical 3P 1 direct 6

600 mm PrismaSeT Pack 250 Pack enclosure ComPact INS125 fixed direct front rotary handle vertical 4P 1 direct 6

600 mm PrismaSeT Pack 250 Pack enclosure ComPact INS160 fixed direct front rotary handle vertical 3P 1 direct 6

600 mm PrismaSeT Pack 250 Pack enclosure ComPact INS160 fixed direct front rotary handle vertical 4P 1 direct 6

600 mm PrismaSeT Pack 250 Pack enclosure ComPact INS40 fixed direct front rotary handle vertical 3P 1 direct 6

600 mm PrismaSeT Pack 250 Pack enclosure ComPact INS40 fixed direct front rotary handle vertical 4P 1 direct 6

600 mm PrismaSeT Pack 250 Pack enclosure ComPact INS63 fixed direct front rotary handle vertical 3P 1 direct 6

600 mm PrismaSeT Pack 250 Pack enclosure ComPact INS63 fixed direct front rotary handle vertical 4P 1 direct 6

600 mm PrismaSeT Pack 250 Pack enclosure Multi9 NG125 without fixed toggle 3P 1 direct 6

600 mm PrismaSeT Pack 250 Pack enclosure Multi9 NG125 without fixed toggle 4P 1 direct 6

600 mm PrismaSeT Pack 250 Pack enclosure Acti 9 C120 with fixed toggle 3P 1 direct 6

600 mm PrismaSeT Pack 250 Pack enclosure Acti 9 C120 with fixed toggle 4P 1
direct 6

600 mm PrismaSeT Pack 250 Pack enclosure Acti 9 iC120 with fixed toggle 3P 1
direct 6

600 mm PrismaSeT Pack 250 Pack enclosure Acti 9 iC120 with fixed toggle 4P 1
direct 6

600 mm PrismaSeT Pack 250 Pack enclosure Multi9 NG125 with fixed toggle 3P 1
direct 6

600 mm PrismaSeT Pack 250 Pack enclosure Multi9 NG125 with fixed toggle 4P 1
direct 6

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.000 cm
Package 1 Width	14.000 cm
Package 1 Length	42.000 cm
Package 1 Weight	532.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	15
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	8.334 kg
Unit Type of Package 3	P12
Number of Units in Package 3	240
Package 3 Height	42.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	144.594 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
Halogen-free status	Halogen free plastic parts product
PVC free	Yes
Silicone-free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins