

# Product datasheet

Specifications



## fuse-switch disconnecter D02 - 2 poles - 63 A

MGN02263

### Main

Range	Acti9
Product name	Acti9 D0
Product or component type	Fuse-switch disconnecter
Device short name	D02
Poles description	2P
Number of protected poles	2
Utilisation category	AC-22A conforming to IEC 60947-3 DC-22B conforming to IEC 60947-3

### Complementary

[In] rated current	63 A
fuse curve	GG AM
Fuse size	15 x 36 mm
Fuse size code	D02
[Ue] rated operational voltage	230...400 V AC 50/60 Hz 110 V DC
[Ui] rated insulation voltage	400 V
[Uimp] rated impulse withstand voltage	6 kV
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	6
Height	88 mm
Width	72 mm
Depth	68 mm
Mechanical durability	8500 cycles open-close
Electrical durability	1500 cycles
Connections - terminals	Screw clamp terminals 1.5...35 mm <sup>2</sup> rigid Screw clamp terminals 1.5...25 mm <sup>2</sup> flexible Screw clamp terminals 1.5...25 mm <sup>2</sup> flexible with cable end
Wire stripping length	14 mm
Tightening torque	3 N.m

### Environment

<b>Standards</b>	IEC 60947-3 EN 60947-1 EN 60947-3 IEC 60269-1 IEC 60947-1 IEC 60269-3
<b>Quality labels</b>	VDE
<b>IP degree of protection</b>	IP20
<b>Ambient air temperature for operation</b>	-5...40 °C
<b>Ambient air temperature for storage</b>	-25...55 °C

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	7.500 cm
<b>Package 1 Width</b>	5.400 cm
<b>Package 1 Length</b>	9.000 cm
<b>Package 1 Weight</b>	269.000 g
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	6
<b>Package 2 Height</b>	8.500 cm
<b>Package 2 Width</b>	9.700 cm
<b>Package 2 Length</b>	32.800 cm
<b>Package 2 Weight</b>	1.672 kg
<b>Unit Type of Package 3</b>	S03
<b>Number of Units in Package 3</b>	36
<b>Package 3 Height</b>	30.000 cm
<b>Package 3 Width</b>	30.000 cm
<b>Package 3 Length</b>	40.000 cm
<b>Package 3 Weight</b>	10.450 kg

## Contractual warranty

<b>Warranty (in months)</b>	18
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

Yes

SCIP Number

B617c31b-ef89-4cf1-9642-26149ac9cf09

### Use Longer



#### Lifetime extension

Repair

No

### Use Again



#### Repack and remanufacture

Take-back

No

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins