

# Product datasheet

Specifications



## TeSys GC - modular contactor - 100 A - 4 NO - coil 24 V AC

GC10040B5

⚠ Discontinued on: 1 Nov 2020

EAN Code: 3389110707717

⚠ Discontinued

### Main

Range	TeSys
Product name	TeSys GC
Product or component type	Modular contactor
Device short name	GC100
Contactor application	Motor control Heating Lighting

### Complementary

Utilisation category	AC-7A
Poles description	4P
power pole contact composition	4 NO
[Ue] rated operational voltage	<= 250 V AC
[Ie] rated operational current	100 A AC-7A
Operating position	30°/vertical
Control circuit type	AC at 50 Hz
[Uc] control circuit voltage	24 V AC 50 Hz
[Uimp] rated impulse withstand voltage	4 kV
[Ith] conventional free air thermal current	100 A (at 50 °C) for power circuit
[Icw] rated short-time withstand current	800 A 40 °C - 10 s for power circuit 250 A 40 °C - 30 s for power circuit
Associated fuse rating	100 A gL at <= 440 V for power circuit
Average impedance	1 mOhm - Ith 100 A 50 Hz for power circuit
[Ui] rated insulation voltage	500 V conforming to IEC 61095 500 V conforming to VDE 0110
Electrical durability	AC-7A: 30000 cycles
Power dissipation per pole	10 W
Control type	Remote control
Mounting mode	Clip-on
Mounting support	DIN rail
Standards	IEC 60947-5 IEC 61095

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

<b>Connections - terminals</b>	Power circuit: screw clamp terminals 1 cable(s) 35 mm <sup>2</sup> flexible without cable end Power circuit: screw clamp terminals 1 cable(s) 35 mm <sup>2</sup> flexible with cable end Power circuit: screw clamp terminals 1 cable(s) 35 mm <sup>2</sup> solid without cable end Power circuit: screw clamp terminals 2 cable(s) 10 mm <sup>2</sup> solid without cable end Control circuit: screw clamp terminals 1 cable(s) 2.5 mm <sup>2</sup> flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 2.5 mm <sup>2</sup> flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 2.5 mm <sup>2</sup> flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 1.5 mm <sup>2</sup> flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 1.5 mm <sup>2</sup> solid without cable end Control circuit: screw clamp terminals 2 cable(s) 1.5 mm <sup>2</sup> solid without cable end
<b>Tightening torque</b>	Control circuit: 0.8 N.m - on screw clamp terminals Power circuit: 3.5 N.m - on screw clamp terminals
<b>Operating time</b>	10...25 ms opening 10...30 ms closing
<b>Mechanical durability</b>	1000000 cycles
<b>Maximum operating rate</b>	300 cyc/h 50 °C
<b>Control circuit voltage limits</b>	Drop-out: 0.2...0.75 U <sub>c</sub> at 50 Hz (at <50 °C) Operational: 0.85...1.1 U <sub>c</sub> at 50 Hz (at <50 °C)
<b>Inrush power in VA</b>	106 VA 50 Hz (at 20 °C)
<b>Hold-in power consumption in VA</b>	13 VA 50 Hz (at 20 °C)
<b>Heat dissipation</b>	4.2 W at 50/60 Hz

## Environment

<b>IP degree of protection</b>	IP40 conforming to VDE 0106 (in enclosure) IP20 conforming to VDE 0106
<b>Protective treatment</b>	TC
<b>Ambient air temperature for operation</b>	-5...50 °C
<b>Ambient air temperature for storage</b>	-40...70 °C
<b>Operating altitude</b>	<= 3000 m
<b>Mechanical robustness</b>	Shocks contactor open: 10 Gn for 11 ms Shocks contactor closed: 15 Gn for 11 ms Vibrations contactor open: 2 Gn, 5...300 Hz Vibrations contactor closed: 3 Gn, 5...300 Hz
<b>Total number of 18 mm modules</b>	6
<b>Height</b>	85 mm
<b>Width</b>	108 mm
<b>Depth</b>	62.5 mm
<b>Net weight</b>	0.78 kg
<b>Quantity per set</b>	Set of 2
<b>Colour</b>	White

## Contractual warranty

<b>Warranty (in months)</b>	18
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Longer



#### Lifetime extension

Repair

No

### Use Again



#### Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins