

Product datasheet

Specifications



reversing contactor - 575 V AC - 115 A - IEC

LC2D115L7

⚠ Discontinued on: 7 Sept 2021

EAN Code: 3389110737912

⚠ Discontinued

Main

Range of product	TeSys D
Product or component type	Reversing contactor
Device short name	LC2D
Contactor application	Motor control
Utilisation category	AC-3 AC-2 AC-4
Control circuit type	AC
Coil type	Standard
Poles description	3P
Pole contact composition	3 NO

Complementary

Assembly style	Ready assembled
Coil technology	Without built-in bidirectional peak limiting diode suppressor
Protective cover	With
Auxiliary contact composition	1 NO + 1 NC
Interlocking type	Mechanical
Overvoltage category	III
Mounting support	Plate Rail
Associated fuse rating	10 A gG for control circuit conforming to IEC 60947-5-1
Mechanical durability	8000000 cycles
Height	158 mm
Width	266 mm
Depth	148 mm
Net weight	6.35 kg

Environment

Standards	EN 60947-4-1 IEC 60947-4-1 CSA C22.2 No 14 IEC 60947-5-1 UL 508 EN 60947-5-1
-----------	---

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product certifications	DNV RINA BV CCC CSA UL GL GOST LROS (Lloyds register of shipping)
Ambient air temperature for operation	-5...60 °C
Ambient air temperature for storage	-60...80 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	23 cm
Package 1 Width	31.5 cm
Package 1 Length	37 cm
Package 1 Weight	6.5 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
EU RoHS Directive	Compliant
PVC free	Yes

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
End of life manual availability	End of Life Information
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins