



stainless steel plug cover, for using ET200ecoPN M12-L in hazardous area zone 2 / 22

General information	
Product description	connector cover for ET200ecoPN M12-L
Suitability for use	accessories for use of the ET200ecoPN M12-L in hazardous area Zone 2/22
Degree and class of protection	
IP degree of protection	IP20
Ambient conditions	
Ambient temperature during assembly, min.	-40 °C
Ambient temperature during assembly, max.	80 °C
Ambient temperature during operation	
• min.	-40 °C
• max.	60 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	80 °C
Mechanics/material	
Material of housing	stainless steel with plastic edge protection
Material property	
• Silicone-free	Yes
Dimensions	
Width	50 mm
Height	200 mm
Depth	110 mm
Weights	
Weight, approx.	710 g
Classifications	

	Version	Classification
eClass	14	27-24-26-92
eClass	12	27-24-26-92
eClass	9.1	27-24-26-92
eClass	9	27-24-26-92
eClass	8	27-24-26-92
eClass	7.1	27-24-26-92
eClass	6	27-24-26-92
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584

Approvals / Certificates

General Product Approval	For use in hazardous locations
--------------------------	--------------------------------

[Manufacturer Declaration](#)



[CCC-Ex](#)



[Miscellaneous](#)

For use in hazardous locations



last modified: 10/22/2025