


Product datasheet

Specifications



passive filter, Altivar, 180A, 400V,
for variable speed drive

VW3A4610

 **End-of-service on:** Nov 24, 2021 AD

 **Discontinued**

Main

Product or component type	Passive filter
Product specific application	Reduction of current harmonics

Complementary

Range compatibility	Altivar 61 Altivar 71
[Us] rated supply voltage	400 V +/- 10 %
power supply frequency	50 Hz +/- 5 %
Quantity per drive	1 filter per drive for ATV61HC11N4 1 filter per drive for ATV71HC11N4
[In] rated current	180 A
Network number of phases	3 phases
THDI	10 % for ATV61HC11N4 motor: 110 kW/150 hp 10 % for ATV71HC11N4 motor: 110 kW/150 hp
Max current	1.5 x nominal current
Efficiency	98 %
Cos phi	1 (150 % of line current) 0.85 (75 % of line current) 0.99 (100 % of line current)
Electrical connection	bare wires diameter: 12.5 mm
Electrical insulation class	Class F
Net weight	103 kg

Environment

IP degree of protection	IP20
Relative humidity	5...85 % without condensation
Ambient air temperature for operation	40...55 °C (with current derating 3 % per °C) 5...40 °C (without current derating)
Ambient air temperature for storage	-25...55 °C
Operating altitude	<= 1000 m without current derating > 1000...4000 m with current derating 5 % per 1000 m

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of Units in Package 1	1
------------------------------	---

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better


Materials and Substances	
EU RoHS Directive	Compliant

Use Longer

Lifetime extension	
Repair	No

Dimensions Drawings

Dimensions



Dimensions in mm

a	a1	b	b1	c	c1	G	G1	J
1060	830	400	390	393	345	395	377	370

Dimensions in in.

a	a1	b	b1	c	c1	G	G1	J
41.73	32.68	15.74	15.35	15.47	13.58	15.55	14.84	14.57

Mounting and Clearance

Mounting Recommendations

Horizontal or Vertical Mounting

