

Product datasheet

Specifications

Motors



AC servo motor BDH - 1.95 N.m - 6000 rpm - untapped shaft - with brake -IP67

BDH0841C25F2A

⚠ Discontinued on: 8 Jul 2022

⚠ Discontinued

EAN Code: 3389118173576

Main

Product or component type	AC servo motors
Component name	BDH
Continuous stall torque	1.95 N.m for LXM15LU60N4 3 phases
Peak stall torque	5.12 N.m for LXM15LU60N4 at 230 V 3 phases 5.12 N.m for LXM15LU60N4 at 400 V 3 phases 5.12 N.m for LXM15LU60N4 at 480 V 3 phases
Nominal output power	300 W for LXM15LU60N4 at 230 V 3 phases 500 W for LXM15LU60N4 at 400 V 3 phases 600 W for LXM15LU60N4 at 480 V 3 phases
Nominal torque	1.8 N.m for LXM15LU60N4 at 480 V 3 phases 1.83 N.m for LXM15LU60N4 at 400 V 3 phases 1.88 N.m for LXM15LU60N4 at 230 V 3 phases
Nominal speed	1500 rpm for LXM15LU60N4 at 230 V 3 phases 2500 rpm for LXM15LU60N4 at 400 V 3 phases 3000 rpm for LXM15LU60N4 at 480 V 3 phases
Maximum mechanical speed	6000 rpm
Product compatibility	LXM15LU60N4 at 230 V 3 phases LXM15LU60N4 at 400 V 3 phases LXM15LU60N4 at 480 V 3 phases
Shaft end	Untapped
IP degree of protection	IP67
Encoder type	2-pole resolver
Speed feedback resolution	65536 points/turn
Holding brake	With
Mounting support	International IEC standard flange
Electrical connection	Rotatable right-angled connectors
Number of poles	10

Complementary

Range compatibility	Lexium 15
Maximum current I _{rms}	4.1 A
Torque constant	1.34 N.m/A at 120 °C
Back emf constant	86.3 V/krpm at 120 °C
Stator resistance	21.7 Ohm at 20 °C
Stator inductance	66.1 mH at 20 °C

Stator electrical time constant	3.05 ms at 20 °C
--	------------------

Maximum radial force Fr	310 N at 6000 rpm 340 N at 5000 rpm 370 N at 4000 rpm 400 N at 3000 rpm 430 N at 2000 rpm 460 N at 1000 rpm
--------------------------------	--

Maximum axial force Fa	0.3 x Fr
-------------------------------	----------

Net weight	2.44 kg
-------------------	---------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No