



Figure similar

SITRANS P DS III / P410, HART, 4-20 mA transmitter for differential pressure and flow PN 32/160 gas 1/liquids 1 art. 3.3 sep ***** Attention, product canceled / successor product P320/P420 available! Please get in touch with your Siemens contact to determine the successor product ***** Measuring cell filling silicone normal cleaning Span: PN 32 (MWP 464 psi): 1 to 20 mbar (0.4015 to 8.03 inH₂O), max. static pressure 32 bar Diaphragm stainless steel parts of measuring cell stainless steel Process connection: 1/4-18 npt mounting thread: 7/16-20 unf Die-cast aluminium housing, process flange bolts stainless steel International design english inscription documentation as cd ATEX (Ex ia + Ex d + Zone 1D/2D) Electric connection and cable inlet: cable gland M20 x1.5 without visible digital indicator (digital display hidden, setting: mA)

Further information

Configurable Products

Technical Data and CAx data (3d-models , eplan.macros) from configurable products cannot shown here. To display the technical data for your device configuration please open PIA LifeCyclePortal and enter there your product number (MLFB). Exemplary 3d-models and eplan-macros are available at the industry imagadatabase. Data for a specific product can be requested with help of a support request.

PIA LifeCyclePortal

<https://pia-portal.automation.siemens.com>

Industry - Image Database

<http://www.automation.siemens.com/bilddb/>

Industry Mall (Online-Order System)

<https://mall.industry.siemens.com>

Information- and Downloadcenter (Catalogs, Brochures, ...)

<http://www.siemens.com/industrial-controls/catalogs>

Support Request

<https://support.industry.siemens.com/my/us/en/requests#createRequest>

last modified:

10/20/2022 