



Figure similar

***** Replacement part ***** SIMATIC S7-400, Interface module IF963-RS232 with RS232 interface for PTP coupling with CP441

Input current		
Current consumption, max.	100 mA	
Power loss		
Power loss, typ.	0.5 W	
Interfaces		
Point-to-point connection		
• Transmission rate, max.	115.2 kbit/s	
• Cable length, max.	15 m	
Dimensions		
Width	20 mm	
Height	70 mm	
Depth	95 mm	
Weights		
Weight, approx.	80 g	
Classifications		
	Version	Classification
eClass	14	27-24-22-08
eClass	12	27-24-22-08
eClass	9.1	27-24-22-08
eClass	9	27-24-22-08
eClass	8	27-24-22-08
eClass	7.1	27-24-22-08
eClass	6	27-24-22-08
ETIM	10	EC001423
ETIM	9	EC001423
ETIM	8	EC001423
ETIM	7	EC001423
IDEA	4	3564
UNSPSC	15	32-15-17-05
Approvals / Certificates		
General Product Approval		EMV



EG-Konf.



UL



RCM

[China RoHS](#)



RCM

EMV

For use in hazardous locations



RCM



ATEX

[EM](#)



IECEX

[Type Examination Certificate](#)



ATEX

Maritime application



[CCS \(China Classification Society\)](#)

last modified:

7/21/2025