

Measurement accessories				
Designation	Use	Description	Reference	Weight kg/ lb
	■ Applications			
Temperature control				
NTC probe	Outside air	- IP 65 - Wall mounting - NTC 10kOhm /25°C	TM1STNTCW69755	0.050/ 0.110
	■ Temperature control: -50...100 °C (-58...212 °F)			
NTC probe	Inside air (room)	- IP 30 - Indoor wall mounting - NTC 10kOhm /25°C	TM1STNTCWN75750	0.050/ 0.110
	■ Temperature control: -25...40 °C (-13...104 °F)			
Humidity control				
Humidity probe	Multi-purpose	- IP 65 - Wall mounting - 4-20 mA	TM1SHC4	0.140/ 0.308
	■ Humidity control: 0...100%			
Humidity & temperature control				
Humidity & temperature probes	Multi-purpose	- IP 65 - Wall mounting - 4-20 mA, NTC 10kOhm /25°C	TM1SHTCN4	0.140/ 0.308
	■ Humidity control: 0...100% ■ Temperature control: -40...60 °C (-40...140 °F)			
	Multi-purpose	- IP 65 - Wall mounting - 2x 4-20 mA	TM1SHTCC4	0.140/ 0.308
	■ Humidity control: 0...100% ■ Temperature control: -40...60 °C (-40...140 °F)			
	Multi-purpose	- IP 65 - Wall mounting - 2x Modbus ports embedded (RS-485 / Modbus RTU)	TM1SHTM4	0.140/ 0.308
	■ Humidity control: 0...100% ■ Temperature control: -40...60 °C (-40...140 °F)			