

Product datasheet

Specifications



servo motor BCH, Lexium 28,
130mm, 600W, 6.63kg.cm², without
oil seal, with key, straight connection

BCH2MM0611CA6C

⚠ Discontinued on: 27 Aug 2020

⚠ Discontinued

Main

Range compatibility	Lexium 28
Device short name	BCH2
Product or component type	Servo motor

Complementary

Maximum mechanical speed	3000 rpm
[Us] rated supply voltage	220 V 110 V
Network number of phases	Three phase Single phase
Continuous stall current	3.77 A
Continuous stall torque	5.73 N.m for LXM28... at 4.5 A, 220 V, single phase 5.73 N.m for LXM28... at 4.5 A, 220 V, three phase 5.73 N.m for LXM28... at 9 A, 110 V, single phase
Continuous power	600 W
Peak stall torque	17.19 N.m for LXM28... at 4.5 A, 220 V, single phase 17.19 N.m for LXM28... at 4.5 A, 220 V, three phase 17.19 N.m for LXM28... at 9 A, 110 V, single phase
Nominal output power	600 W for LXM28... at 4.5 A, 220 V, single phase 600 W for LXM28... at 4.5 A, 220 V, three phase 600 W for LXM28... at 9 A, 110 V, single phase
Nominal torque	5.73 N.m for LXM28... at 4.5 A, 220 V, single phase 5.73 N.m for LXM28... at 4.5 A, 220 V, three phase 5.73 N.m for LXM28... at 9 A, 110 V, single phase
Nominal speed	1000 rpm for LXM28... at 4.5 A, 220 V, single phase 1000 rpm for LXM28... at 4.5 A, 220 V, three phase 1000 rpm for LXM28... at 9 A, 110 V, single phase
Maximum current Irms	13.44 A for LXM28... at 0.6 kW, 220 V 13.44 A for LXM28... at 0.6 kW, 110 V
Maximum permanent current	4.1 A
Product compatibility	LXM28... servo drive motor at 0.6 kW, 220 V, single phase LXM28... servo drive motor at 0.6 kW, 220 V, three phase LXM28... servo drive motor at 0.6 kW, 110 V, single phase
Shaft end	Keyed
Shaft diameter	22 mm
Shaft length	45 mm
Key width	8 mm
Feedback type	20 bits single turn absolute encoder

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Holding brake	Without
Mounting support	Asian standard flange
Motor flange size	130 mm
Electrical connection	Connector MIL
Torque constant	1.52 N.m/A at 20 °C
Back emf constant	92 V/krpm at 20 °C
Rotor inertia	6.63 kg.cm²
Stator resistance	1.93 Ohm at 20 °C
Stator inductance	24.9 mH at 20 °C
Stator electrical time constant	12.9 ms at 20 °C
Maximum radial force Fr	670 N at 1000 rpm
Maximum axial force Fa	200 N
Brake pull-in power	19.7 W
Type of cooling	Natural convection
Length	147 mm
Number of motor stacks	1
Centring collar diameter	110 mm
Centring collar depth	8 mm
Number of mounting holes	4
Mounting holes diameter	9.2 mm
Circle diameter of the mounting holes	145 mm
Distance shaft shoulder-flange	8 mm
Net weight	7 kg
Sizing reference	BCH2
Network number of phases	1
Accuracy error [angular]	0.044 °
Temperature copper hot	135 °C
Temperature magnet hot	100 °C
Temperature magnet rt	20 °C

Environment

IP degree of protection	IP54 IM B5, IM V1 IP50 IM V3
Ambient air temperature for operation	-20...40 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	18.1 cm
Package 1 Width	23.0 cm
Package 1 Length	36.0 cm

Package 1 Weight	8.07 kg
------------------	---------

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better



Materials and Packaging

EU RoHS Directive

[Compliant By Exemption](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture


End of life manual availability

[End of Life Information](#)

Dimensions Drawings

Dimensions

Dimensions of Motor




	mm	in.
L (without holding brake)	147	5.79
L (with holding brake)	183	7.2
Z	94.5	3.72

Performance Curves

Torque/Speed Curves with 230 V Single/Three Phase Supply Voltage

Servo Motor with LXM28AU02 Servo Drive



- 1 : Peak torque
- 2 : Continuous torque