

SITRANS P DS III / P410, HART, 4-20 mA transmitter for differential pressure and flow PN 32/160 gas 1/liquids 1 art. 3.3 sep ***** Attention, product canceled / successor product P320/P420 available! Please get in touch with your Siemens contact to determine the successor product ***** Measuring cell filling silicone normal cleaning Span: PN 160 (MWP 2320 psi): 6 to 600 mbar (2.409 to 240.9 inH2O), max. static pressure 160 bar Diaphragm stainless steel parts of measuring cell stainless steel Process connection: 1/4-18 npt mounting thread: 7/16-20 unf Die-cast aluminium housing, process flange bolts stainless steel Standard design . Explosion protection fm + csa Electric connection and cable inlet: cable gland 1/2-14 npt Housing cover with window (setting: mA) With steel mounting bracket Rating plate inscriptions in Englisch, pressure units in H2O resp. psi

Further information

Configurable Products

Technical Data and CAx data (3d-models , eplan.macros) from configurable products cannot shown here. To display the technical data for your device configuration please open PIA LifeCyclePortal and enter there your product number (MLFB). Exemplary 3d-models and eplan-macros are available at the industry imagadatabase. Data for a specific product can be requested with help of a support request.

PIA LifeCyclePortal

<https://pia-portal.automation.siemens.com>

Industry - Image Database

<http://www.automation.siemens.com/bilddb/>

Industry Mall (Online-Order System)

<https://mall.industry.siemens.com>

Information- and Downloadcenter (Catalogs, Brochures, ...)

<http://www.siemens.com/industrial-controls/catalogs>

Support Request

<https://support.industry.siemens.com/my/us/en/requests#createRequest>

last modified:

9/22/2024 