

# Product datasheet

Specifications



## TeSys LRD thermal time delay relays 400V

LT3TK400

⚠ Discontinued on: 1 Nov 2020

⚠ Discontinued

### Main

Range of the product	TeSys
Product name	TeSys LRD
Device short name	LT3TK
Product or component type	Relay
Device application	Electronic application
Relay application	Time delay relay

### Complementary

[Us] rated supply voltage	400 V AC/DC
Voltage range	0.85...1.1 Us
Contacts type and composition	2 C/O multi voltage
[Ithe] conventional enclosed thermal current	5 A
Ambient air temperature for operation	-25...60 °C
Control type	Automatic reset Manual reset
Hold-in power consumption in W	47...51 W
Height	85 mm
Width	81 mm
Depth	80 mm

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.5 cm
Package 1 Width	10 cm
Package 1 Length	13.5 cm
Package 1 Weight	465 g

### Contractual warranty

Warranty (in months)	18
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

EU RoHS Directive

[Compliant](#)

### Use Longer



#### Lifetime extension

Repair

No

### Use Again



#### Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins