

Product datasheet

Specifications

4 Crimp lugs - for copper cable 120 mm² and phase barriers



LV429256

⚠ Discontinued on: 1 Dec 2024

⚠ To be discontinued

Main

Product or component type	Crimp lug
Accessory / separate part category	Connection accessory
Range compatibility	ComPacT NSX100 ComPacT NSX160 ComPacT NSX250 ComPacT NSX100 DC ComPacT NSX160 DC ComPacT NSX250 DC EasyPact CVS100...250 ComPact INS250 ComPact Compact INV100...250 FuPact FuPacT ISFT FuPact Fupact INF
Poles description	4P
Quantity per set	Set of 4
[In] rated current	250 A

Complementary

Provided equipment	Interphase barriers
Conductor material	Copper
Connections - terminals	Crimp lug1 cable(s) 120 mm ²

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.000 cm
Package 1 Width	12.000 cm
Package 1 Length	16.000 cm
Package 1 Weight	298.200 g
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Height	11.000 cm
Package 2 Width	20.000 cm
Package 2 Length	35.000 cm
Package 2 Weight	3.762 kg
Unit Type of Package 3	S03

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of Units in Package 3	24
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	7.557 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	2 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	1 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.6 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
Halogen-free status	Product contains halogen above thresholds

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	83
End of life manual availability	No need of specific recycling operations
Take-back	Nej