

Product datasheet

Specifications



miniature circuit breaker - Domae - 1P - 4A - 220...240 V - C curve - 4.5 kA

DOM12252SNI

! Discontinued

! Discontinued on: 1 Dec 2020

! End-of-service on: 30 Dec 2021

Main

Device application	Distribution
Range	Domae
Product or component type	Miniature circuit-breaker
Poles description	1P
Number of protected poles	1
[In] rated current	4 A
Network type	AC
Curve code	C
Breaking capacity	4500 A at 230 V AC 50 Hz conforming to IEC 60898-1

Complementary

Network frequency	50 Hz
[Ue] rated operational voltage	220...240 V AC 50 Hz
Control type	Toggle
Mounting mode	Clip-on
Mounting support	DIN rail
Comb busbar and distribution block compatibility	YES
9 mm pitches	2
Colour	Grey

Environment

Standards	SNI 04-6507.1 IEC 60898-1
Product certifications	SNI

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.5 cm
Package 1 Width	1.8 cm
Package 1 Length	8.5 cm

Package 1 Weight

106 g



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Packaging

Packaging without single use plastic

Yes

EU RoHS Directive

[Compliant By Exemption](#)

Halogen-free status

Halogen free product

Use Longer



Lifetime extension

Repair

No