

Product datasheet

Specifications



Standard motor mechanism module (MCH), fixed ComPacT NS630b to NS1600, 277VAC 50/60Hz

33686

Main

Device short name	MCH
Product or component type	Motor mechanism
Device application	Automatic spring charging
Range compatibility	ComPacT NS630b...1600
Control type	Standard
[Uc] control circuit voltage	277 V AC 50/60 Hz
circuit breaker mounting mode	Fixed
circuit breaker frame rated current	630 A 1000 A 1600 A 800 A 1250 A

Complementary

Control signal type	Impulse Maintained
circuit breaker response time	60 ms +/- 10 ms open 60 ms +/- 10 ms closed
Maximum operating frequency	<= 3 cycles per minute
Maximum power consumption in VA	180 VA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	3 kg

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	22 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Carbon footprint of the manufacturing phase [A1 to A3]	15 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.4 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.6 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0.1 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	7 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	7c479875-b986-4ae2-a2e9-f5f369faf4e7
Halogen-free status	Halogen free plastic parts product

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	73
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins