

Product data sheet

Specifications



power plug in relay, Harmony
Electromechanical Relays, 30A,
1NO, with LED, lockable test button,
24V DC

725AXXB4L-24D

Main

Range of product	Harmony Electromechanical Relays
Series name	725 series
Product or component type	Plug-in relay
Contacts type and composition	1 NO
Relay type	Power relay
status LED	With
[Uc] control circuit voltage	24 V DC
Network frequency	50/60 Hz
[Ithe] conventional enclosed thermal current	30 A
Local signalling	LED indicator lockable test button Flag

Complementary

class number	725
Minimum switching current	100 mA 5 V DC
Nominal input voltage	19.2...26.4 V DC
Electrical durability	100000 cycles resistive IEC
Dielectric strength	4000 V AC between coil and contact
Control type	Lockable test button
Coil resistance	300 Ohm
Average coil consumption	1.90 W
Wire stripping length	0.3 in (8 mm)
Response time	30 ms
Associated fuse rating	32 A gG at 400 V coordination type 2 for power circuit
Short-circuit current	3 kA
Average pole impedance	2 mOhm
Maximum switching voltage	240 V CE 277 V UL
Drop-out voltage threshold	DC
Rated power in W	1.5 kW 120 V tungsten
Rated power in hp	3 hp 277 V AC 1.5 hp 120 V AC

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

[Ie] rated operational current	30 A 277 V AC on resistive load)UL 30 A 240 V AC general purpose)UL 30 A 30 V DC on resistive load)UL 30 A 240 V AC on resistive load)IEC 30 A 28 V DC on resistive load)IEC
Mechanical durability	5000000 cycles
Mounting support	Plug-in
Contacts material	Silver alloy contacts
Shape of pin	Flat (faston type)
Width	1.3 in (33.1 mm)
Height	2.0 in (50 mm)
Depth	2.09 in (53.05 mm)
Net weight	4.2 oz (120 g)

Environment

Standards	IEC 60947-1 UL 60947-4-1A
Product certifications	UL CSA CE
Ambient air temperature for storage	-67...212 °F (-55...100 °C)
Ambient air temperature for operation	-4...131 °F (-20...55 °C)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.94 in (4.94 cm)
Package 1 Width	1.30 in (3.31 cm)
Package 1 Length	2.67 in (6.77 cm)
Package 1 Weight	4.2 oz (120.0 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	3.0 in (7.6 cm)
Package 2 Width	5.7 in (14.6 cm)
Package 2 Length	12.6 in (31.9 cm)
Package 2 Weight	2.6 lb(US) (1.2 kg)
Unit Type of Package 3	CAR
Number of Units in Package 3	100
Package 3 Height	13.0 in (33.0 cm)
Package 3 Width	12.2 in (31.0 cm)
Package 3 Length	14.2 in (36.0 cm)
Package 3 Weight	26.5 lb(US) (12.0 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Longer


Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No

Dimensions Drawings


Dimensions



- (1) : Back View
- (2) : Side View
- (3) : Bottom view
- (4) : Top view

Connections and Schema

Wiring



Technical Illustration

Dimensions




Image of product / Alternate images

Alternative





Image of product in real life situation

