

# Product datasheet

Specifications



## Circuit breaker Masterpact MTZ2 16H1 - 1600 A - 4P drawout - w/o Micrologic

LV848280

### Main

|                                |                                                                                                                                                                                                                                                                          |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range                          | MasterPacT                                                                                                                                                                                                                                                               |
| Product name                   | MasterPact MTZ2                                                                                                                                                                                                                                                          |
| Device short name              | MTZ2 16 H1                                                                                                                                                                                                                                                               |
| Product or component type      | Circuit breaker                                                                                                                                                                                                                                                          |
| Device application             | Power distribution protection                                                                                                                                                                                                                                            |
| Poles description              | 4P                                                                                                                                                                                                                                                                       |
| Neutral position               | Left                                                                                                                                                                                                                                                                     |
| Control unit                   | Without control unit                                                                                                                                                                                                                                                     |
| Product compatibility          | control unit MicroLogic 2.0 X<br>control unit MicroLogic 5.0 X<br>control unit MicroLogic 6.0 X<br>control unit MicroLogic 7.0 X<br>control unit MicroLogic 2.0 Xi<br>control unit MicroLogic 5.0 Xi<br>control unit MicroLogic 6.0 Xi<br>control unit MicroLogic 7.0 Xi |
| [In] rated current             | 1600 A at 40 °C                                                                                                                                                                                                                                                          |
| Performance type               | H1 66 kA 415 V AC                                                                                                                                                                                                                                                        |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz                                                                                                                                                                                                                                                        |
| Suitability for isolation      | Yes conforming to EN/IEC 60947-2                                                                                                                                                                                                                                         |
| Selectivity category           | Category B                                                                                                                                                                                                                                                               |
| Control type                   | Push-button                                                                                                                                                                                                                                                              |
| Mounting mode                  | Drawout                                                                                                                                                                                                                                                                  |

### Complementary

|                                                      |                                                                                                                                      |
|------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| [Icu] rated ultimate short-circuit breaking capacity | 66 kA at 220/415 V AC 50/60 Hz<br>66 kA at 440 V AC 50/60 Hz<br>66 kA at 500/525 V AC 50/60 Hz<br>66 kA at 660/690 V AC 50/60 Hz     |
| [Ics] rated service breaking capacity                | 66 kA at 220/415 V AC 50/60 Hz<br>66 kA at 440 V AC 50/60 Hz<br>66 kA at 500/525 V AC 50/60 Hz<br>66 kA at 660/690 V AC 50/60 Hz     |
| [Icw] rated short-time withstand current             | 66 kA 0.5 s<br>66 kA 1 s<br>36 kA 3 s                                                                                                |
| [Icm] rated short-circuit making capacity            | 145 kA 220/415 V AC at 50/60 Hz<br>145 kA 440 V AC at 50/60 Hz<br>145 kA 500/525 V AC at 50/60 Hz<br>145 kA 660/690 V AC at 50/60 Hz |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                                        |                                                                                                                                                                                                                                                                                                                                                  |
|----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sensor rating                          | 800 A<br>1000 A<br>1250 A<br>1600 A                                                                                                                                                                                                                                                                                                              |
| [Ui] rated insulation voltage          | 1000 V AC 50/60 Hz                                                                                                                                                                                                                                                                                                                               |
| [Uimp] rated impulse withstand voltage | 12 kV                                                                                                                                                                                                                                                                                                                                            |
| Power dissipation in W                 | 390 W                                                                                                                                                                                                                                                                                                                                            |
| Maximum breaking time                  | 25 ms                                                                                                                                                                                                                                                                                                                                            |
| Maximum closing response time          | 70 ms                                                                                                                                                                                                                                                                                                                                            |
| Mounting support                       | Rails<br>Base plate                                                                                                                                                                                                                                                                                                                              |
| Upside connection                      | Front<br>Rear                                                                                                                                                                                                                                                                                                                                    |
| Downside connection                    | Front<br>Rear                                                                                                                                                                                                                                                                                                                                    |
| Connection pitch                       | 115 mm                                                                                                                                                                                                                                                                                                                                           |
| Mechanical durability                  | 25000 cycles with periodic preventive maintenance                                                                                                                                                                                                                                                                                                |
| Electrical durability                  | 10000 cycles 440 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>10000 cycles 690 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>AC-23A: 10000 cycles 440 V AC 50/60 Hz conforming to EN/IEC 60947-3<br>AC-23A: 10000 cycles 690 V AC 50/60 Hz conforming to EN/IEC 60947-3<br>AC-3: 6000 cycles 440/690 V AC 50/60 Hz conforming to EN/IEC 60947-3 |
| Height                                 | Drawout circuit breaker with chassis: 439 mm<br>Drawout circuit breaker without chassis: 300 mm                                                                                                                                                                                                                                                  |
| Width                                  | Drawout circuit breaker with chassis: 556 mm<br>Drawout circuit breaker without chassis: 493 mm                                                                                                                                                                                                                                                  |
| Depth                                  | Drawout circuit breaker with chassis: 403 mm<br>Drawout circuit breaker without chassis: 300 mm                                                                                                                                                                                                                                                  |
| Net weight                             | 120 kg                                                                                                                                                                                                                                                                                                                                           |
| Standards                              | EN/IEC 60947-1<br>EN/IEC 60947-2<br>EN/IEC 60947-2 Annex H<br>IEC 61557-12                                                                                                                                                                                                                                                                       |
| Product certifications                 | CE<br>IECEE CB Scheme                                                                                                                                                                                                                                                                                                                            |

## Environment

|                                       |                                                            |
|---------------------------------------|------------------------------------------------------------|
| IP degree of protection               | IP30 conforming to EN 60529                                |
| Pollution degree                      | 3 conforming to IEC 60947-1                                |
| Ambient air temperature for operation | -25...70 °C                                                |
| Ambient air temperature for storage   | -40...85 °C                                                |
| Operating altitude                    | 0...2000 m without derating<br>2000...5000 m with derating |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 30.5 cm |
| Package 1 Width              | 29.5 cm |
| Package 1 Length             | 49.5 cm |

|                  |           |
|------------------|-----------|
| Package 1 Weight | 47.653 kg |
|------------------|-----------|

## Logistical informations

|                   |    |
|-------------------|----|
| Country of origin | FR |
|-------------------|----|

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|                                                        |                                               |
|--------------------------------------------------------|-----------------------------------------------|
| Total lifecycle Carbon footprint                       | 3 021 kg CO2 eq.                              |
| Environmental Disclosure                               | <a href="#">Product Environmental Profile</a> |
| Carbon footprint of the manufacturing phase [A1 to A3] | 629 kg CO2 eq.                                |
| Carbon footprint of the distribution phase [A4]        | 14 kg CO2 eq.                                 |
| Carbon footprint of the installation phase [A5]        | 16 kg CO2 eq.                                 |
| Carbon footprint of the use phase [B2, B3, B4, B6]     | 2 157 kg CO2 eq.                              |
| Carbon footprint of the end-of-life phase [C1 to C4]   | 206 kg CO2 eq.                                |

## Use Better



### Materials and Substances

|                                        |                                                                                                                                       |
|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Packaging made with recycled cardboard | Yes                                                                                                                                   |
| Packaging without single use plastic   | No, we have minimized the use of plastic in the packaging in compliance with regulations and considering quality and safety standards |
| SCIP Number                            | F31d8a4d-e9cb-4afc-bf2c-5965742ce772                                                                                                  |
| EU RoHS Directive                      | <a href="#">Compliant By Exemption</a>                                                                                                |
| REACH Regulation                       | <a href="#">Reference contains Substances of Very High Concern above the threshold</a>                                                |
| Halogen-free status                    | Product contains halogen above thresholds                                                                                             |
| PVC free                               | Yes                                                                                                                                   |
| Silicone-free                          | No                                                                                                                                    |

## Use Longer



### Lifetime extension

|        |    |
|--------|----|
| Repair | No |
|--------|----|

## Use Again



### Repack and remanufacture

|                                 |                                                                                                                                                                                                                 |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Recyclability potential, in %   | 71                                                                                                                                                                                                              |
| End of life manual availability | <a href="#">End of Life Information</a>                                                                                                                                                                         |
| Take-back                       | Yes                                                                                                                                                                                                             |
| WEEE Label                      |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

