

Product datasheet

Specifications

Motors



AC servo motor BDH - 11.4 N.m -
6000 rpm - key shaft - without brake
- IP67

BDH1083P32A2B

EAN Code: 3389118186859

! Discontinued

Main

Product or component type	AC servo motors
Component name	BDH
Continuous stall torque	11.4 N.m for LXM15MD56N4 3 phases
Peak stall torque	22.2 N.m for LXM15MD56N4 at 230 V 3 phases
Nominal output power	3000 W for LXM15MD56N4 at 230 V 3 phases
Nominal torque	6.2 N.m for LXM15MD56N4 at 230 V 3 phases
Nominal speed	5000 rpm for LXM15MD56N4 at 230 V 3 phases
Maximum mechanical speed	6000 rpm
Product compatibility	LXM15MD56N4 at 230 V 3 phases
Shaft end	Keyed
IP degree of protection	IP67
Encoder type	Absolute multiturn SinCos Hiperface
Speed feedback resolution	1048576 points/turn x 4096 turns
Holding brake	Without
Mounting support	NEMA flange
Electrical connection	Rotatable right-angled connectors
Number of poles	10

Complementary

Range compatibility	Lexium 15
Maximum current Irms	40.59 A
Torque constant	0.6 N.m/A at 120 °C
Back emf constant	38.4 V/krpm at 120 °C
Stator resistance	0.27 Ohm at 20 °C
Stator inductance	1.3 mH at 20 °C
Stator electrical time constant	4.81 ms at 20 °C
Maximum radial force Fr	300 N at 6000 rpm 325 N at 5000 rpm 350 N at 4000 rpm 375 N at 3000 rpm 400 N at 2000 rpm 425 N at 1000 rpm
Maximum axial force Fa	0.3 x Fr

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Net weight

7.4 kg



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No