

Product datasheet

Specifications



Power relay, SE Relays, 30A, 1NO, 12VDC, LED, flag indicator, locking push button, blade terminal, plug-in socket mount

725AXXB4L-12D

! Discontinued

! Discontinued on: 12 Jun 2024

Main

Range of product	Harmony Electromechanical Relays
Series name	Power
Product or component type	Plug-in relay
Contacts type and composition	1 NO
Network frequency	50/60 Hz
Local signalling	LED indicator Flag

Complementary

class number	725
Minimum switching current	100 mA at 5 V DC
Nominal input voltage	9.6...13.2 V DC
Electrical durability	100000 cycles resistive load conforming to IEC
Dielectric strength	4000 V AC between coil and contact
Control type	Lockable test button
Coil resistance	75 Ohm
Average coil consumption	1.90 W
Wire stripping length	8 mm
Response time	30 ms
Associated fuse rating	32 A gG at 400 V coordination type 2 for power circuit
Short-circuit current	3 kA
Average pole impedance	2 mOhm
Maximum switching voltage	240 V conforming to CE 277 V conforming to UL
Drop-out voltage threshold	DC
Rated power in W	1.5 kW 120 V tungsten
Rated power in hp	3 hp at 277 V AC 1.5 hp at 120 V AC

[Ie] rated operational current	30 A at 277 V AC (on resistive load) conforming to UL 30 A at 240 V AC (general purpose) conforming to UL 30 A at 30 V DC (on resistive load) conforming to UL 30 A at 240 V AC (on resistive load) conforming to IEC 30 A at 28 V DC (on resistive load) conforming to IEC
--------------------------------	---

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Mechanical durability	5000000 cycles
Mounting support	Plug-in
Contacts material	Silver alloy contacts
Width	33.1 mm
Height	50 mm
Depth	53.05 mm
Net weight	120 g

Environment

Standards	IEC 60947-1 UL 60947-4-1A
Product certifications	UL CSA CE
Ambient air temperature for storage	-55...100 °C
Ambient air temperature for operation	-20...55 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.31 cm
Package 1 Width	5 cm
Package 1 Length	5.08 cm
Package 1 Weight	120 g



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better


Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant

Use Longer

Lifetime extension	
Repair	No

Dimensions Drawings


Dimensions



- (1) : Back View
- (2) : Side View
- (3) : Bottom view
- (4) : Top view

Connections and Schema

Wiring



Technical Illustration

Dimensions




Image of product / Alternate images

Alternative





Image of product in real life situation

