

SIMATIC S7-1500, CM PTP RS232 HF communications module for serial connection RS-232, freeport, 3964(R), USS, Modbus RTU master, device, 115200 bit/s, 9-pin D-sub plug

General information	
Product type designation	CM PtP RS 232 HF
Product function	
• I&M data	Yes; I&M 0
• Fast startup	Yes
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	V18 with HSP 0367 / V19; configurable with older TIA Portal versions as 6ES7541-1AD00-0AB0
• STEP 7 configurable/integrated from version	V5.5 SP2 with GSD file
• PROFIBUS from GSD version/GSD revision	- / -
• PROFINET from GSD version/GSD revision	GSDML V2.42
Installation type/mounting	
Rail mounting	Yes; S7-1500 mounting rail
Supply voltage	
Design of the power supply	system power supply
Input current	
Current consumption (rated value)	50 mA; From the backplane bus
Power	
Power consumption from the backplane bus	0.75 W
Power loss	
Power loss, typ.	0.6 W
Address area	
Address space per module	
• Inputs	8 byte; performance mode: 32 byte
• Outputs	0 byte; performance mode: 32 byte
Interface types	
RS 232	
• Transmission rate, max.	115.2 kbit/s
• Cable length, max.	15 m
• RS 232 auxiliary signals	RTS, CTS, DTR, DSR, RI, DCD
Protocols	
Integrated protocols	
Freeport	
— Telegram length, max.	4 kbyte
— Bits per character	7 or 8
— Number of stop bits	1 or 2 bit
— Parity	None, even, odd, always 1, always 0, any
3964 (R)	
— Telegram length, max.	4 kbyte
— Bits per character	7 or 8
— Number of stop bits	1 or 2 bit
— Parity	None, even, odd, always 1, always 0, any
Modbus RTU master	
— Address area	1 to 247, extended 1 to 65535
— max. number of devices	1
Modbus RTU device	
— Address area	1 to 247, extended 1 to 65535
Telegram buffer	

• Buffer memory for telegrams	8 kbyte	
• Number of telegrams which can be buffered	255	
<b>Interrupts/diagnostics/status information</b>		
Diagnostics function	Yes	
<b>Alarms</b>		
• Diagnostic alarm	Yes	
• Hardware interrupt	No	
<b>Diagnoses</b>		
• Wire-break	Yes	
<b>Diagnostics indication LED</b>		
• RUN LED	Yes; green LED	
• ERROR LED	Yes; red LED	
• Receive RxD	Yes; Yellow LED	
• Transmit TxD	Yes; Yellow LED	
<b>Potential separation</b>		
between backplane bus and interface	Yes	
<b>Isolation</b>		
Isolation tested with	707 V DC (type test)	
<b>Security</b>		
signed firmware update	Yes	
<b>Ambient conditions</b>		
<b>Ambient temperature during operation</b>		
• horizontal installation, min.	-30 °C	
• horizontal installation, max.	60 °C	
• vertical installation, min.	-30 °C	
• vertical installation, max.	40 °C	
<b>Altitude during operation relating to sea level</b>		
• Installation altitude above sea level, max.	5 000 m; restrictions for installation altitudes > 2 000 m, see ET 200MP system manual	
<b>Absolute humidity</b>		
• dew point, min.	-60 °C	
<b>Decentralized operation</b>		
to SIMATIC S7-300	Yes	
to SIMATIC S7-400	Yes	
to SIMATIC S7-1500	Yes	
to standard PROFINET controller	Yes	
<b>Dimensions</b>		
Width	35 mm	
Height	147 mm	
Depth	127 mm	
<b>Weights</b>		
Weight, approx.	0.22 kg	
<b>Classifications</b>		
	<b>Version</b>	<b>Classification</b>
eClass	14	27-24-22-08
eClass	12	27-24-22-08
eClass	9.1	27-24-22-08
eClass	9	27-24-22-08
eClass	8	27-24-22-08
eClass	7.1	27-24-22-08
eClass	6	27-24-22-08
ETIM	10	EC001423
ETIM	9	EC001423
ETIM	8	EC001423
ETIM	7	EC001423
<b>Approvals / Certificates</b>		

General Product Approval

[Manufacturer Declaration](#)



[Miscellaneous](#)

[China RoHS](#)



General Product Approval

EMV

For use in hazardous locations



[FM](#)

[CCC-Ex](#)



For use in hazardous locations

Maritime application

[Type Examination Certificate](#)



[Miscellaneous](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)



last modified:

12/18/2025