

Product datasheet

Specifications



voltage release Compact MN - 24 V DC

29410

⚠ Discontinued on: 2 Apr 2021

⚠ Discontinued

Main

Range	ComPact
Range of product	NR400...630 NS400...630 NB400...600 NSF150...250 NS400...630 DC NS100...250 NS100...250 DC NR100...250 NS125E NSJ400...600
Device short name	MN
Product or component type	Voltage release
Device application	Control
Voltage release type	Undervoltage release
[Uc] control circuit voltage	24 V DC
Range compatibility	ComPact ComPact NS ComPact Compact NB ComPact Compact NR ComPact Compact NSF ComPact Compact NSJ

Complementary

Operating threshold	0.35...0.7 Un opening 0.85 Un closing
Response time	< 50 ms
Supply holding power	< 5 W
Auxiliary connection terminal	Screw terminal 0...1.5 mm ²

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins