

Quick coupling plug NPHS-S6-M-G18

Part number: 8059257

FESTO



 General operating condition

Data sheet

| Feature | Value |
|--|---|
| Nominal width | 5.5 mm |
| Operating pressure for entire temperature range | -0.095 MPa ... 1.2 MPa |
| Operating pressure for entire temperature range | -0.95 bar ... 12 bar |
| Operating pressure for entire temperature range | -13.775 psi ... 174 psi |
| Normal nominal flow rate (normalized to DIN 1343) | 875 l/min ... 1238 l/min |
| Nominal flow rate standardized according to ISO 8778 | 948.5 l/min ... 1342 l/min |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:-:-] |
| Information on operating and pilot media | Lubricated operation possible |
| Corrosion resistance class (CRC) | 1 - Low corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Ambient temperature | -10 °C ... 60 °C |
| Nominal tightening torque | 3.5 Nm |
| Tolerance for nominal tightening torque | ±10% |
| Product weight | 19 g |
| Pneumatic connection 1 | External thread G1/8 |
| Note on materials | RoHS compliant |
| Material of threaded seal | PA66-GF30 / TPE-U |
| Information on materials | Galvanized steel |