

Product data sheet

Specifications



TeSys SK mini contactor - 4P (4 NO) - AC-1 - 690 V 20 A - 110 V AC coil

LC1SKGC400F7

⚠ Discontinued on: Jul 12, 2021

⚠ Discontinued

Main

Range	TeSys
Product name	TeSys SK
Product or Component Type	Mini contactor
Device short name	LC1SKGC
Contactor application	Resistive load
Utilisation category	AC-1
power pole contact composition	4P
Pole contact composition	4 NO
[Ie] rated operational current	20 A (at <122 °F (50 °C)) AC AC-1
[Ue] rated operational voltage	Power circuit 690 V AC 50/60 Hz

Complementary

Control circuit type	AC 50/60 Hz
[Uc] control circuit voltage	110 V AC 50/60 Hz
[Ith] conventional free air thermal current	20 A (at 131 °F (55 °C)) for power circuit
Irms rated making capacity	85 A AC conforming to NF C 63-110 85 A AC conforming to IEC 60947
Rated breaking capacity	68 A at <= 400 V conforming to NF C 63-110 68 A at <= 400 V conforming to IEC 60947
[Icw] rated short-time withstand current	60 A 131 °F (55 °C) for power circuit
Associated fuse rating	20 A gl at <= 440 V for power circuit
Average impedance	4 mOhm - Ith 20 A 50 Hz for power circuit
[Ui] rated insulation voltage	Power circuit 690 V BS 5424 Power circuit 690 V IEC 60947 Power circuit 690 V UL 508 Power circuit 690 V VDE 0110 group C Power circuit 690 V CSA C22.2 No 14
Mounting Support	Panel Rail
Standards	EN/IEC 60947-4-1 UL 60947-4-1 CSA C22.2 No 60947-4-1
Product Certifications	CB Scheme CE UKCA EAC cULus

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Connections - terminals	connector 1 0.002...0.009 in² (1.5...6 mm²)solid connector 2 0.002...0.006 in² (1.5...4 mm²)solid connector 1 0.0008...0.009 in² (0.5...6 mm²)flexible without cable end connector 2 0.0005...0.004 in² (0.35...2.5 mm²)flexible without cable end connector 1 0.0005...0.009 in² (0.35...6 mm²)flexible with cable end connector 2 0.0005...0.002 in² (0.35...1.5 mm²)flexible with cable end
Tightening torque	Power circuit 7.08 lbf.in (0.8 N.m) connector pozidriv No 1
Operating time	6...8 ms coil de-energisation and NO opening 7...14 ms coil energisation and NO closing
Mechanical durability	10 Mcycles
Maximum operating rate	1200 cyc/h
Control circuit voltage limits	Operational: 0.85...1.1 Uc at 50/60 Hz (at <131 °F (55 °C)) Drop-out: 0.2...0.75 Uc at 50/60 Hz (at <131 °F (55 °C))
Inrush power in VA	23 VA 50/60 Hz (at 68 °F (20 °C))
Hold-in power consumption in VA	4.9 VA 50/60 Hz (at 68 °F (20 °C))
Heat dissipation	1.5 W 50/60 Hz

Environment

IP degree of protection	IP2X VDE 0106
Protective treatment	TC IEC 60068 TC DIN 50015
Ambient Air Temperature for Operation	-4...122 °F (-20...50 °C)
Ambient Air Temperature for Storage	-58...158 °F (-50...70 °C)
Operating altitude	6561.68 ft (2000 m) without derating
Height	2.3 in (58 mm)
Width	1.8 in (45 mm)
Depth	2.2 in (56 mm)
Net Weight	0.386 lb(US) (0.175 kg)

Ordering and shipping details

Category	18400-WORLD SERVICE PARTS(CONTACTORS)
Discount Schedule	CP10
GTIN	3389110563764
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.5 in (6.4 cm)
Package 1 Width	2.4 in (6 cm)
Package 1 Length	1.9 in (4.8 cm)
Package weight(Lbs)	5.9 oz (167 g)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained](#) >

[How we assess product sustainability](#) >

Use Better

 Materials and Substances	
EU RoHS Directive	Compliant

Use Longer

 Lifetime extension	
Repair	No

Use Again

 Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.