

Product datasheet

Specifications



TeSys D & F - capacitive delayed opening devices - 220....240 V - 50/60 Hz

LAZR90M

⚠ Discontinued on: 1 Dec 2024

⚠ To be discontinued

Main

Range	TeSys
Product or component type	Capacitive delayed opening devices
Device short name	LAZR
Product compatibility	LC1F115...F630 LC1D09...D80
[Us] rated supply voltage	220...240 V AC

Complementary

[Uc] control circuit voltage	305 V DC 348 V DC
Time delay range	0.5...10 s
Height	77 mm
Width	55 mm
Depth	114 mm
Net weight	0.215 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.900 cm
Package 1 Width	8.700 cm
Package 1 Length	12.000 cm
Package 1 Weight	238.000 g

Contractual warranty

Warranty (in months)	18
----------------------	----

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
REACH Regulation	REACH Declaration

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins