

# Product datasheet

Specifications



## enclosed DOL starter TeSys - GV2-LC - 4 A

GV2LC0208

EAN Code: 3389110948189

! Discontinued

### Main

Range of product	TeSys
Device short name	GV2LC
Motor starter type	Non reversing
Product or component type	Enclosed DOL starter
Poles description	3P
Motor starter composition	With circuit breaker
Trip unit technology	Magnetic
Thermal protection adjustment range	4 A
Control type	Rotary handle black
Enclosure material	Polycarbonate

### Complementary

[Ue] rated operational voltage	690 V
Breaking capacity	100 kA Icu at 220...230 V conforming to IEC 60947-2 100 kA Icu at 400...415 V conforming to IEC 60947-2 100 kA Icu at 440 V conforming to IEC 60947-2 100 kA Icu at 500 V conforming to IEC 60947-2
Magnetic tripping limit	13 x In +/- 20 %
cable entry	2 x 25 mm ISO at top 2 x 20 mm ISO at bottom 2 x 25 mm ISO at bottom 2 x 20 mm ISO at top
Locking options description	1 to 3 padlocks Ø 8 Padlock in OFF position
Width	88 mm
Height	166 mm
Depth	173 mm
Net weight	0.78 kg

### Environment

Standards	IEC 60947-4 VDE 0660-102 EN 60947 IEC 60439-1
IP degree of protection	IP54 conforming to IEC 60529

# Contractual warranty

---

Warranty (in months)

18



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Longer



#### Lifetime extension

Repair

No

### Use Again



#### Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins