

# Product datasheet

Specifications



## Control relay, Easy TeSys Control, CAE, 4NO, <=690V, 440V AC coil

CAE40R6

⚠ Discontinued on: 1 Nov 2020

⚠ Discontinued

### Main

Range	Easy TeSys
Range of product	Easy TeSys Control Relay
Product or component type	Control relay
Device short name	CAE
Contactors application	Control circuit
Colour	Grey (RAL 7011)

### Complementary

Utilisation category	AC-15 AC-14
Pole contact composition	4 NO
[Ue] rated operational voltage	<= 690 V AC
Control circuit type	AC at 60 Hz
[Uc] control circuit voltage	440 V AC 60 Hz
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947
[Ith] conventional free air thermal current	10 A (at 40 °C)
Irms rated making capacity	140 A at 690 V AC conforming to IEC 60947-5-1
[Icw] rated short-time withstand current	120 A - 500 ms 140 A - 100 ms
Associated fuse rating	10 A gG at 690 V conforming to IEC 60947-5-1
[Ui] rated insulation voltage	690 V conforming to IEC 60947-5-1
Mounting support	Rail Plate
Connections - terminals	Screw clamp terminals 1 1...2.5 mm <sup>2</sup> - cable stiffness: flexible without cable end Screw clamp terminals 2 1...2.5 mm <sup>2</sup> - cable stiffness: flexible without cable end Screw clamp terminals 1 1...2.5 mm <sup>2</sup> - cable stiffness: flexible with cable end Screw clamp terminals 2 1...2.5 mm <sup>2</sup> - cable stiffness: flexible with cable end Screw clamp terminals 1 1...2.5 mm <sup>2</sup> - cable stiffness: solid without cable end Screw clamp terminals 2 1...2.5 mm <sup>2</sup> - cable stiffness: solid without cable end
Recommended tightening torque	1.2 N.m - on screw clamp terminals - with screwdriver Philips No 2
Control circuit voltage limits	Drop-out: 0.3...0.6 U <sub>c</sub> Operational: 0.85...1.1 U <sub>c</sub> at 60 Hz
Operating time	12...22 ms coil energisation and NO closing 6...17 ms coil de-energisation and NO closing
Mechanical durability	10 Mcycles

<b>Maximum operating rate</b>	180 cyc/mn
<b>Inrush power in VA</b>	70 VA 60 Hz (at 20 °C)
<b>Hold-in power consumption in VA</b>	8 VA 60 Hz (at 20 °C)
<b>Minimum switching voltage</b>	17 V
<b>Minimum switching current</b>	5 mA
<b>Insulation resistance</b>	> 10 MOhm
<b>Mechanical robustness</b>	Shocks control relay open: 7 Gn for 11 ms Shocks control relay closed: 10 Gn for 11 ms Vibrations control relay open: 1.5 Gn, 5...300 Hz Vibrations control relay closed: 3 Gn, 5...300 Hz
<b>Height</b>	74 mm
<b>Width</b>	45 mm
<b>Depth</b>	80 mm
<b>Net weight</b>	0.28 kg

## Environment

<b>Standards</b>	EN/IEC 60947-1 EN/IEC 60947-5-1 GB/T 14048.1 GB/T 14048.5
<b>Product certifications</b>	CB Scheme CCC CE EAC
<b>IP degree of protection</b>	IP2X conforming to IEC 60529
<b>Protective treatment</b>	TH conforming to IEC 60068
<b>Ambient air temperature for operation</b>	-20...70 °C
<b>Ambient air temperature for storage</b>	-60...80 °C
<b>Operating altitude</b>	3000 m without derating

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1

## Contractual warranty

<b>Warranty (in months)</b>	18
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

[EU RoHS Directive](#)

Compliant

### Use Longer



#### Lifetime extension

Repair

No