

Product data sheet

Specifications



Multi 9 - C60 UL489 - MCB - 3P - 1 A - D Curve - 480Y/277 V - 10 kA - tunnel ter

MGN61356

! Discontinued

! Discontinued on: Nov 6, 2025

! End-of-service on: Dec 31, 2025

Main

Range	Multi9
Product name	Multi9 C60
Product or component type	Miniature circuit-breaker
Device short name	C60 UL489
Device application	Distribution
Poles description	3P
Number of protected poles	3
[In] rated current	1 A 77 °F (25 °C)
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	D
Breaking capacity	10 kA AIR 480Y/277 V AC UL 489 10 kA AIR 480Y/277 V AC CSA C22.2 No 5.2 10 kA Icu 480Y/277 V AC EN/IEC 60947-2 10 kA Icu 480Y/277 V AC GB 14048.2
Suitability for isolation	Yes EN/IEC 60947-2
Standards	GB 14048.2 EN/IEC 60947-2 UL 489 CSA C22.2 No 5
Product certifications	CSA CCC IEC UL

Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	480Y/277 V AC
Magnetic tripping limit	12 x In +/- 20 % AC
Limitation class	3 EN/IEC 60947-2
[Ui] rated insulation voltage	500 V AC EN/IEC 60947-2
[Uimp] rated impulse withstand voltage	6 kVEN/IEC 60947-2
Contact position indicator	Yes
Control type	Toggle

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Local signalling	ON/OFF indication
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	6
Height	5.6 in (141 mm)
Width	2.1 in (54 mm)
Depth	2.7 in (68.7 mm)
Net weight	0.73 lb(US) (0.33 kg)
Colour	Grey
Mechanical durability	20000 cycles
Electrical durability	10000 cycles
Provision for padlocking	Padlockable
Connections - terminals	Tunnel type terminal top or bottom) - 1 0.002...0.002 in² (1...1.5 mm²) AWG 18...AWG 16) - rigid Tunnel type terminal top or bottom) - 2 0.002...0.002 in² (1...1.5 mm²) AWG 18...AWG 16) - rigid
Tightening torque	7.08 lbf.in (0.8 N.m) top or bottom

Environment

IP degree of protection	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529
Pollution degree	3 EN/IEC 60947-2
Overvoltage category	IV
Tropicalisation	2 IEC 60068-1
Relative humidity	95 % 131 °F (55 °C)
Operating altitude	2000 m
Ambient air temperature for operation	-22...158 °F (-30...70 °C)
Ambient air temperature for storage	-40...176 °F (-40...80 °C)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.953 in (7.501 cm)
Package 1 Width	0.709 in (1.801 cm)
Package 1 Length	5.6 in (14.1 cm)
Package 1 Weight	17.600 oz (498.952 g)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

Yes

SCIP Number

40a4e715-7fff-45ff-88bf-38212f6a80a5

EU RoHS Directive

[Compliant](#)

REACH Regulation

[Reference contains Substances of Very High Concern above the threshold](#)

Halogen content performance

Halogen free product

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins