

EZ Meter-Pak[®] Meter Centers EZM Main Device Types and Configurations

Fusible Switch Main Devices (Fed from Overhead or Underground Service)



EZM3800FS

Service Type	Ampere Rating	Catalog Numbers ¹	Molded Case Switch ²	Line Phase Terminal Wire Range (AWG-kcmil, Al/Cu)	Line Neutral Terminal Wire Range (AWG-kcmil, Al/Cu)	Service Grounding Terminal Wire Range (AWG-kcmil, Al/Cu)
--------------	---------------	------------------------------	---------------------------------	---	---	--

1Ø IN Fusible Switch Main Devices (Fed from Overhead or Underground Service)

1Ø3W, 120/240 Vac	400	EZM1400FS	LHP26000M ³	(1) 1/0-600 or (2) 1/0-250 ⁴	(1) 1/0-600 or (2) 1/0-250 ⁵	(1) 6-300
	600	EZM1600FS	MHP260006M ³	(3) 3/0-500 ⁴	(4) 3/0-500 ⁶	(1) 6-300
	800	EZM1800FS	MHP260008M ³	(3) 3/0-500 ⁴	(4) 3/0-500 ⁶	(1) 6-300
	1200	EZM11200FS	PHF260000M	(4) 1/0-750 or (8) 1/0-250	(4) 1/0-750 or (8) 1/0-250	(1) 6-300

3Ø IN Fusible Switch Main Devices (Fed from Overhead or Underground Service)

3Ø4W, 208Y/120 Vac or 240/120 Vac Delta	400	EZM3400FS	LHP36000M ³	(1) 1/0-600 or (2) 1/0-250 ⁴	(1) 1/0-600 or (2) 1/0-250 ⁵	(1) 6-300
	600	EZM3600FS	MHP360006M ³	(3) 3/0-500 ⁴	(4) 3/0-500 ⁶	(1) 6-300
	800	EZM3800FS	MHP360008M ³	(3) 3/0-500 ⁴	(4) 3/0-500 ⁶	(1) 6-300

¹ Fuses not included. Order 300 V Class T fuses.

² Supplied factory-installed.

³ Handle extension available, order kit AHXL. Handle is hinged, allowing it to be tucked under door on cover.

⁴ Alternate lug kits are available for use on line side of molded case switch (refer to most current Digest).

⁵ Alternate neutral lug available, order one MMLK500 for use of two 3/0 AWG-500 kcmil Al/Cu (includes three two-barrel lugs). Neutral will accommodate one two-barrel lug only.

⁶ Alternate neutral lugs available, order one MMLK250 for use on 1/0 AWG-600 kcmil Al/Cu or two 1/0 AWG-250 kcmil Al/Cu (includes three two-barrel lugs). Neutral will accommodate two two-barrel lugs only.



EZM3800FS

Fusible Switch Main Devices (Fed from Underground Service Only)

Service Type	Ampere Rating	Catalog Numbers ¹	Molded Case Switch ²	Line Phase and Neutral Lug Landing Pads provided for use with Crimp-Type Lugs (Two-Hole Mounting) Quantity of Lugs Permitted per Pad	Service Grounding Terminal Wire Range (AWG-kcmil, Al/Cu)
--------------	---------------	------------------------------	---------------------------------	--	--

1Ø IN Fusible Switch Main Devices (Fed from Underground Service Only)

1Ø3W, 120/240 Vac	400	EZM1400FSU ³	LHF26000M ⁴	1 ⁵	(1) 6-300
	600	EZM1600FSU ³	MHF260006M ⁴	2 ⁵	(1) 6-300
	800	EZM1800FSU ³	MHF260008M ⁴	2 ⁵	(1) 6-300
	1200	EZM11200FSU ³	PHF260000M	3 ⁵	(1) 6-300

3Ø IN Fusible Switch Main Devices (Fed from Underground Service Only)

3Ø4W, 208Y/120 Vac or 240/120 Vac Delta	400	EZM3400FSU ³	LHF36000M ⁴	1 ⁵	(1) 6-300
	600	EZM3600FSU ³	MHF360006M ⁴	2 ⁵	(1) 6-300
	800	EZM3800FSU ³	MHF360008M ⁴	2 ⁵	(1) 6-300

¹ Fuses not included. Order 300 V Class T fuses.

² Supplied factory-installed.

³ Meets Electrical Utility Service Equipment Requirements Committee (EUSERC) Standards for West Coast based utilities.

⁴ Handle extension available, order kit AHXL. Handle is hinged, allowing it to be tucked under door on cover.

⁵ Order lugs separately.