

Product datasheet

Specifications



function module, TransferPacT,
source availability output, 2NO+2NC
dry contact, 250VAC or 30VDC

TPCDIO19

Main

Range of product	TransferPacT
Product or component type	I/O module
Device application	Signalling

Complementary

Auxiliary contact composition	2 NO + 2 NC
Signalling function	Status indication
Local signalling	LED (green) for power available from mains
Auxiliary connection terminal	Screw clamp terminal 0.05...2.6 mm ²
Mounting mode	Plug-in
[Ui] rated insulation voltage	300 V AC
Tightening torque	0.6 N.m +/- 0.1 N.m
Maximum output voltage	AC: 250 V DC: 30 V
Height	56.5 mm
Width	20 mm
Depth	69 mm
Maximum output current	5 A
Accessory / separate part category	Signalling accessory

Environment

IP degree of protection	IP20
Pollution degree	3

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.4 cm
Package 1 Width	10.5 cm
Package 1 Length	4.4 cm
Package 1 Weight	103 g
Unit Type of Package 2	S02
Number of Units in Package 2	12

Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	1.613 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

SCIP Number

Cbd5c90f-9537-4f0e-b5dd-d4cb5b67b442

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

Take-back

No