

Product datasheet

Specifications



circuit breaker Masterpact NW20H2
- 2000 A - 4 poles - drawout - w/o
trip unit

48295

Price: 11,473,882.16 NGN

Main

Range	MasterPacT
Product name	MasterPact NW
Circuit breaker name	MasterPact NW20H2
Product or component type	Circuit breaker
Device application	Power distribution protection
Poles description	4P
Neutral position	Left
Control unit	Without control unit
[In] rated current	2000 A at 40 °C
Performance type	H2 100 kA 440 V AC
[Ue] rated operational voltage	690 V AC 50/60 Hz
Suitability for isolation	Yes conforming to EN/IEC 60947-2
Selectivity category	Category B
Control type	Push-button
Mounting mode	Drawout

Complementary

[Icu] rated ultimate short-circuit breaking capacity	100 kA at 220/415 V AC 50/60 Hz 100 kA at 440 V AC 50/60 Hz 85 kA at 525 V AC 50/60 Hz 85 kA at 690 V AC 50/60 Hz
[Ics] rated service breaking capacity	100 kA at 220/415 V AC 50/60 Hz 100 kA at 440 V AC 50/60 Hz 85 kA at 525 V AC 50/60 Hz 85 kA at 690 V AC 50/60 Hz
[Icw] rated short-time withstand current	85 kA 1 s 75 kA 3 s
[Icm] rated short-circuit making capacity	220 kA 220/415 V AC at 50/60 Hz 187 kA 440 V AC at 50/60 Hz 187 kA 525 V AC at 50/60 Hz 187 kA 690 V AC at 50/60 Hz
Integrated instantaneous protection (DIN in kA peak)	171...209 kA
Sensor rating	1000 A 2000 A
[Ui] rated insulation voltage	1000 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	12 kV
Power dissipation in W	470 W

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Maximum breaking time	25 ms
Maximum closing response time	70 ms
Mounting support	Backplate Rails
Upside connection	Front Rear
Downside connection	Front Rear
Connection pitch	115 mm
Mechanical durability	10000 cycles without maintenance 20000 cycles with maintenance
Electrical durability	6000 cycles 690 V AC 50/60 Hz without maintenance conforming to EN/IEC 60947-2 8000 cycles 440 V AC 50/60 Hz without maintenance conforming to EN/IEC 60947-2 AC-23A: 6000 cycles 690 V AC 50/60 Hz without maintenance conforming to EN/IEC 60947-3 AC-23A: 8000 cycles 440 V AC 50/60 Hz without maintenance conforming to EN/IEC 60947-3 AC-3: 6000 cycles 440/690 V AC 50/60 Hz without maintenance conforming to EN/IEC 60947-3
Height	439 mm
Width	556 mm
Depth	395 mm
Net weight	120 kg
Standards	EN/IEC 60947-1 EN/IEC 60947-2
Product certifications	CE CCC EAC

Environment

IP degree of protection	IP30 conforming to IEC 60529
Pollution degree	4 conforming to IEC 60664-1
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C
Operating altitude	0...2000 m without derating 2000 m...5000 m with derating

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30.5 cm
Package 1 Width	29.5 cm
Package 1 Length	49.5 cm
Package 1 Weight	49.502 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	3 378 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	582 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	14 kg CO2 eq.
Carbon footprint of the installation phase [A5]	20 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	2 553 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	209 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No, we have minimized the use of plastic in the packaging in compliance with regulations and considering quality and safety standards
SCIP Number	6a3c1e0b-44cb-4a11-80eb-a083722777c1
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
Halogen-free status	Product contains halogen above thresholds
PVC free	Yes
Silicone-free	No

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	69
End of life manual availability	End of Life Information
Take-back	Nej
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

