

# Product datasheet

Specifications



## Contactor, Easy TeSys Control, LC1E, 4P(2NO+2NC), AC-1, <=415V, 25A, 24V

LC1E09008B7IN

! Discontinued

! Discontinued on: 30 Sept 2022

! End-of-service on: 20 Dec 2021

### Main

Range	Easy TeSys
Range of product	Easy TeSys Control
Product or component type	Contactor
Device short name	LC1E
Contactor application	Resistive load
Utilisation category	AC-1
Poles description	4P
[Ue] rated operational voltage	Power circuit: <= 690 V AC 50/60 Hz
[Ie] rated operational current	25 A (at <40 °C) at <= 415 V AC AC-1 for power circuit
[Uc] control circuit voltage	24 V AC 50/60 Hz

### Complementary

Pole contact composition	2 NO + 2 NC
Irms rated making capacity	90 A at 440 V AC for power circuit conforming to IEC 60947-4-1
Rated breaking capacity	72 A at 440 V for power circuit conforming to IEC 60947
[Icw] rated short-time withstand current	105 A 40 °C - 10 s for power circuit 61 A 40 °C - 60 s for power circuit 30 A 40 °C - 600 s for power circuit
Associated fuse rating	12 A gG at <= 690 V coordination type 1 for power circuit conforming to IEC 60947-5-1
Average impedance	2.5 mOhm - Ith 25 A 50 Hz for power circuit
Power dissipation per pole	0.2 W AC-3 1.6 W AC-1
[Ui] rated insulation voltage	690 V conforming to IEC 60947-4-1
Overvoltage category	III
Pollution degree	3
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947
Mechanical durability	10000000 cycles
Electrical durability	1400000 cycles AC-3 150000 cycles AC-1
Control circuit type	AC at 50/60 Hz

<b>Control circuit voltage limits</b>	0.85...1.1 U <sub>c</sub> (-5...55 °C):operational 50/60 Hz 0.3...0.6 U <sub>c</sub> (-5...55 °C):drop-out 50/60 Hz
<b>Inrush power in VA</b>	95 VA 50 Hz cos phi 0.75 (at 20 °C) 95 VA 60 Hz cos phi 0.75 (at 20 °C)
<b>Hold-in power consumption in VA</b>	8.5 VA 50 Hz cos phi 0.3 (at 20 °C) 8.5 VA 60 Hz cos phi 0.3 (at 20 °C)
<b>Heat dissipation</b>	2...3 W for control circuit
<b>Operating time</b>	12...22 ms on closing 4...19 ms on opening
<b>Maximum operating rate</b>	1800 cyc/h 60 °C
<b>Connections - terminals</b>	Power circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 2 1...2.5 mm <sup>2</sup> - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 1 1...6 mm <sup>2</sup> - cable stiffness: solid without cable end Power circuit: screw clamp terminals 2 1...4 mm <sup>2</sup> - cable stiffness: solid without cable end Control circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 1...4 mm <sup>2</sup> - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 2 1...2.5 mm <sup>2</sup> - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 1...6 mm <sup>2</sup> - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 1...4 mm <sup>2</sup> - cable stiffness: solid without cable end
<b>Tightening torque</b>	Power circuit: 1.2 N.m Control circuit: 1.2 N.m
<b>Minimum switching voltage</b>	17 V for control circuit
<b>Minimum switching current</b>	5 mA for control circuit
<b>Insulation resistance</b>	> 10 MOhm for control circuit
<b>Non-overlap time</b>	1.5 ms on energisation guaranteed between NC and NO contact 1.5 ms on de-energisation guaranteed between NC and NO contact
<b>Mounting support</b>	DIN rail Plate

## Environment

<b>Standards</b>	EN/IEC 60947-1 EN/IEC 60947-4-1 EN/IEC 60947-5-1 GB/T 14048.1 GB/T 14048.4 GB/T 14048.5
<b>Product certifications</b>	CB Scheme CCC CE EAC
<b>IP degree of protection</b>	IP2X conforming to IEC 60529
<b>Protective treatment</b>	TH (pollution degree 3) conforming to IEC 60068
<b>Permissible ambient air temperature around the device</b>	-20...70 °C at U <sub>c</sub> -60...80 °C storage -5...55 °C operation
<b>Operating altitude</b>	3000 m
<b>Fire resistance</b>	850 °C conforming to IEC 60695-2-1

---

<b>Mechanical robustness</b>	Vibrations contactor open (1.5 Gn, 5...300 Hz) Vibrations contactor closed (3 Gn, 5...300 Hz) Shocks contactor open (7 Gn for 11 ms) Shocks contactor closed (10 Gn for 11 ms)
<b>Height</b>	74 mm
<b>Width</b>	45 mm
<b>Depth</b>	80 mm
<b>Net weight</b>	0.34 kg

---

## Packing Units

---

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	8 cm
<b>Package 1 Width</b>	4.5 cm
<b>Package 1 Length</b>	7.4 cm
<b>Package 1 Weight</b>	340 g

---

## Contractual warranty

---

<b>Warranty (in months)</b>	18
-----------------------------	----

---



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

## Use Better



### Materials and Substances

EU RoHS Directive

[Compliant](#)

## Use Longer



### Lifetime extension

Repair

No

## Use Again



### Repack and remanufacture

End of life manual availability

[End of Life Information](#)