

# Product datasheet

Specifications



## EasyPact TVS contactor 4P(2 NO + 2 NC) - AC-1 - <= 415 V 80A - 110 V AC coil

LC1E65008F7

⚠ Discontinued on: 01 Nov 2020

⚠ Discontinued

### Main

|                                |                                                        |
|--------------------------------|--------------------------------------------------------|
| Range                          | Easy TeSys                                             |
| Range of product               | Easy TeSys Control                                     |
| Product or component type      | Contactor                                              |
| Device short name              | LC1E                                                   |
| Contactor application          | Resistive load                                         |
| Utilisation category           | AC-1                                                   |
| Poles description              | 4P                                                     |
| [Ue] rated operational voltage | Power circuit: <= 690 V AC 50/60 Hz                    |
| [Ie] rated operational current | 80 A (at <55 °C) at <= 440 V AC AC-1 for power circuit |
| [Uc] control circuit voltage   | 110 V AC 50/60 Hz                                      |

### Complementary

|                                             |                                                                                        |
|---------------------------------------------|----------------------------------------------------------------------------------------|
| Pole contact composition                    | 2 NO + 2 NC                                                                            |
| [Ith] conventional free air thermal current | 80 A (at 55 °C) for power circuit                                                      |
| Irms rated making capacity                  | 650 A at 440 V AC for power circuit conforming to IEC 60947-4-1                        |
| Rated breaking capacity                     | 520 A at 440 V for power circuit conforming to IEC 60947                               |
| [Icw] rated short-time withstand current    | 520 A 40 °C - 10 s for power circuit<br>260 A 40 °C - 60 s<br>110 A 40 °C - 600 s      |
| Associated fuse rating                      | 125 A gG at <= 690 V coordination type 1 for power circuit conforming to IEC 60947-5-1 |
| Average impedance                           | 1 mOhm - Ith 80 A 50 Hz for power circuit                                              |
| Power dissipation per pole                  | 4.2 W AC-3<br>6.4 W AC-1                                                               |
| [Ui] rated insulation voltage               | 690 V conforming to IEC 60947-4-1                                                      |
| Overvoltage category                        | III                                                                                    |
| Pollution degree                            | 3                                                                                      |
| [Uimp] rated impulse withstand voltage      | 6 kV conforming to IEC 60947                                                           |
| Mechanical durability                       | 5000000 cycles                                                                         |
| Electrical durability                       | 350000 cycles AC-1<br>900000 cycles AC-3                                               |
| Control circuit type                        | AC at 50/60 Hz                                                                         |

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Control circuit voltage limits  | 0.85...1.1 Uc (-5...55 °C):operational 50/60 Hz<br>0.3...0.6 Uc (-5...55 °C):drop-out 50/60 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Inrush power in VA              | 160 VA 50 Hz cos phi 0.75 (at 20 °C)<br>140 VA 60 Hz cos phi 0.75 (at 20 °C)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Hold-in power consumption in VA | 15 VA 50 Hz cos phi 0.3 (at 20 °C)<br>13 VA 60 Hz cos phi 0.3 (at 20 °C)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Heat dissipation                | 6...10 W for control circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Operating time                  | 20...26 ms on closing<br>8...12 ms on opening                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Maximum operating rate          | 1200 cyc/h 60 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Connections - terminals         | Control circuit: screw clamp terminals 1 1...4 mm² - cable stiffness: flexible without cable end<br>Control circuit: screw clamp terminals 2 1...4 mm² - cable stiffness: flexible without cable end<br>Control circuit: screw clamp terminals 1 1...4 mm² - cable stiffness: flexible with cable end<br>Control circuit: screw clamp terminals 2 1...2.5 mm² - cable stiffness: flexible with cable end<br>Control circuit: screw clamp terminals 1 1...4 mm² - cable stiffness: solid without cable end<br>Control circuit: screw clamp terminals 2 1...4 mm² - cable stiffness: solid without cable end<br>Power circuit: screw clamp terminals 1 2.5...25 mm² - cable stiffness: flexible with cable end<br>Power circuit: screw clamp terminals 2 2.5...10 mm² - cable stiffness: flexible with cable end<br>Power circuit: screw clamp terminals 1 2.5...25 mm² - cable stiffness: solid without cable end<br>Power circuit: screw clamp terminals 2 2.5...16 mm² - cable stiffness: solid without cable end |
| Tightening torque               | Control circuit: 1.2 N.m<br>Power circuit: 5 N.m                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Insulation resistance           | > 10 MOhm for control circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Mounting support                | DIN rail<br>Plate                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

## Environment

|                                                       |                                                                                                                                                                                        |
|-------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standards                                             | EN/IEC 60947-1<br>EN/IEC 60947-4-1<br>EN/IEC 60947-5-1<br>GB/T 14048.1<br>GB/T 14048.4<br>GB/T 14048.5                                                                                 |
| Product certifications                                | CB Scheme<br>CCC<br>CE<br>EAC                                                                                                                                                          |
| IP degree of protection                               | IP2X conforming to IEC 60529                                                                                                                                                           |
| Protective treatment                                  | TH (pollution degree 3) conforming to IEC 60068-2-30 test Db                                                                                                                           |
| Permissible ambient air temperature around the device | -20...70 °C at Uc<br>-60...80 °C storage<br>-5...55 °C operation                                                                                                                       |
| Operating altitude                                    | 3000 m without derating                                                                                                                                                                |
| Fire resistance                                       | 850 °C conforming to IEC 60695-2-1                                                                                                                                                     |
| Mechanical robustness                                 | Vibrations contactor open (1.5 Gn, 5...300 Hz)<br>Vibrations contactor closed (3 Gn, 5...300 Hz)<br>Shocks contactor open (6 Gn for 11 ms)<br>Shocks contactor closed (7 Gn for 11 ms) |
| Height                                                | 127 mm                                                                                                                                                                                 |
| Width                                                 | 85 mm                                                                                                                                                                                  |

|            |        |
|------------|--------|
| Depth      | 125 mm |
| Net weight | 1.3 kg |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 12.5 cm |
| Package 1 Width              | 8.5 cm  |
| Package 1 Length             | 12.5 cm |
| Package 1 Weight             | 1.65 kg |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

|  Environmental footprint |                                               |
|-----------------------------------------------------------------------------------------------------------|-----------------------------------------------|
| Total lifecycle Carbon footprint                                                                          | 1 084 kg CO2 eq.                              |
| Environmental Disclosure                                                                                  | <a href="#">Product Environmental Profile</a> |
| Carbon footprint of the manufacturing phase [A1 to A3]                                                    | 9 kg CO2 eq.                                  |
| Carbon footprint of the distribution phase [A4]                                                           | 2 kg CO2 eq.                                  |
| Carbon footprint of the installation phase [A5]                                                           | 0 kg CO2 eq.                                  |
| Carbon footprint of the use phase [B2, B3, B4, B6]                                                        | 1 071 kg CO2 eq.                              |
| Carbon footprint of the end-of-life phase [C1 to C4]                                                      | 2 kg CO2 eq.                                  |

### Use Better

|  Materials and Substances |                                      |
|-------------------------------------------------------------------------------------------------------------|--------------------------------------|
| Packaging made with recycled cardboard                                                                      | Yes                                  |
| Packaging without single use plastic                                                                        | Yes                                  |
| <a href="#">EU RoHS Directive</a>                                                                           | Compliant                            |
| SCIP Number                                                                                                 | 4ca4954b-5710-4949-8440-15cb0afd6d31 |
| REACH Regulation                                                                                            | <a href="#">REACH Declaration</a>    |

### Use Longer

|  Lifetime extension |    |
|--------------------------------------------------------------------------------------------------------|----|
| Repair                                                                                                 | No |

### Use Again

|  Repack and remanufacture |                                                                                                                                                                                                                 |
|--------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Recyclability potential, in %                                                                                | 48                                                                                                                                                                                                              |
| End of life manual availability                                                                              | <a href="#">End of Life Information</a>                                                                                                                                                                         |
| Take-back                                                                                                    | No                                                                                                                                                                                                              |
| WEEE Label                                                                                                   |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Offer Marketing Illustration

Product benefits / Features

---



Easy TeSys Contactors  
Range Accessories



Mechanical  
interlock



Auxiliary  
contact block



Time delay auxiliary  
contact block



Terminal block



Suppressor  
module

Offer Marketing Illustration

Product benefits / Features

---

Easy TeSys  
Contactors



**Designed for the essential**  
Deliver the best balance between performance and budget without any compromise on quality



**Easy to use**  
Easier to install and operate with multi-standard screws



**Cost-effective**  
Provides a cost-effective solution to a simple application



Offer Marketing Illustration

Product benefits / Features

Easy TeSys Contactors  
Technical Benefits



- 9 sizes cover common applications from 6A to 630A.
- Designed to meet the requirements of Electro-domestic and HVAC applications.
- Various Relay Coil Voltages; A.C.
- It can cover -5°C to 55°C working temperature and mounted by DIN-rail, No derating up to 3000m altitude.
- 2.2kW to 335kW (AC3/400V)
- Multi-standards certified (IEC, CCC, EAC) and Green Premium compliant (RoHs/Reach).

Technical Illustration

Assembly's dimensions

