

Product data sheet

Specifications



Ultra compact starter, TeSys Hybrid, 3P, 500VAC, 3kW at 400V, 110 to 230VAC

LZ1H6X5FU

⚠ Discontinued on: Feb 27, 2023

⚠ Discontinued

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	TeSys
Product name	TeSys Hybrid
Device short name	LZ1H
Product or Component Type	Ultra-compact starter
Motor starter type	Direct on line
Poles description	3P
[Ue] rated operational voltage	500 V AC
[Ie] rated operational current	6.5 A 500 V AC-53A 9 A 500 V AC-51 4.5 A 500 V AC-53A mounting side by side 6 A 500 V AC-51 mounting side by side
Thermal protection adjustment range	1.5...9 A
Motor power kW	1.5 kW 220 V AC 0.65 1.5 kW 230 V AC 0.65 2.2 kW 380 V AC 0.65 3 kW 400 V AC 0.65 3 kW 415 V AC 0.65 3 kW 440 V AC 0.65 3 kW 500 V AC 0.65
Maximum Horse Power Rating	1 hp 200 V AC 1.5 hp 230 V AC 3 hp 460 V AC
[Uc] control circuit voltage	110...230 V AC 50/60 Hz
Thermal overload class	Class 10A IEC 60947-4-2

Complementary

Auxiliary contact composition	1 C/O fault signalling
Control circuit voltage limits	85...253 V AC
Current consumption	<= 4 mA 110...230 V AC
Reset	Manual Automatic reset Electrical reset
Electrical durability	30 Mcycles
Maximum operating rate	120 cyc/mn AC-51 50 % 6 cyc/mn AC-53A 50 %
Mounting Mode	By clips
Mounting Support	DIN rail

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Connections - terminals	screw clamp terminals 1 0.0003...0.004 in² (0.2...2.5 mm²) rigid screw clamp terminals 1 0.0004...0.004 in² (0.25...2.5 mm²) flexible - with cable end screw clamp terminals 1 0.0003...0.004 in² (0.2...2.5 mm²) flexible - without cable end
Tightening torque	4.4...5.3 lbf.in (0.5...0.6 N.m) flat Ø 2.5 mm screwdriver 0.1 in (3 mm)
Certifications	CULus CE
Standards	UL 60947-4-1 IEC 60947-4-2
[Ui] rated insulation voltage	500 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	4 kV
Pollution degree	2
Width	0.9 in (22.5 mm)
Height	3.9 in (99 mm)
Depth	4.5 in (114.5 mm)
Product Weight	7.5 oz (212 g)

Environment

IP degree of protection	IP20
Protective treatment	TC
Ambient air temperature for operation	-13...86 °F (-25...30 °C) without derating 86...158 °F (30...70 °C) with derating
Ambient Air Temperature for Storage	-40...176 °F (-40...80 °C)

Ordering and shipping details

Category	US10I1222349
Discount Schedule	0I12
GTIN	3606485421155
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.4 in (3.6 cm)
Package 1 Width	4.6 in (11.7 cm)
Package 1 Length	4.7 in (12.0 cm)
Package weight(Lbs)	9.1 oz (258.0 g)
Unit Type of Package 2	S01
Number of Units in Package 2	10
Package 2 Height	5.9 in (15.0 cm)
Package 2 Width	5.9 in (15.0 cm)
Package 2 Length	15.7 in (40.0 cm)
Package 2 Weight	6.105 lb(US) (2.769 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained](#) >

[How we assess product sustainability](#) >

Use Better

Materials and Substances	
EU RoHS Directive	Compliant
California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.