

Product datasheet

Specifications



bar-mounted contactor - TeSys LC1-BP -2 poles - AC-1 1000V 2000 A - coil 415 VAC

LC1BP32N13

⚠ Discontinued on: May 11, 2020 AD

⚠ Discontinued

Main

Range	TeSys
Product name	TeSys B
Product or component type	Contactor
Device short name	LC1BP
Contactor application	Motor-heating-lighting
Utilisation category	AC-1
Control circuit type	AC
Coil type	Standard
Poles description	2P
Pole contact composition	2 NO
[Ie] rated operational current	2000 A (at <40 °C) AC AC-1 for power circuit
Auxiliary contact composition	1 NO + 3 NC
[Uc] control circuit voltage	415 V AC 50...400 Hz

Complementary

Protective cover	With
Auxiliary contacts type	type instantaneous 1 NO + 3 NC
Control circuit voltage limits	Operational: 0.85...1.1 Uc Drop-out: 0.35...0.5 Uc
[Ui] rated insulation voltage	1000 V - for power circuit conforming to IEC 60158-1 1000 V - for power circuit conforming to IEC 60947-4 1500 V - for power circuit conforming to VDE 0110 group C
Connections - terminals	Power circuit: bars 3 x - busbar cross section: 100 x 5 mm
Tightening torque	Power circuit: 35 N.m - on bars
[Ue] rated operational voltage	Power circuit: <= 1000 V AC 50/60 Hz
[Ith] conventional free air thermal current	2000 A (at 40 °C) for power circuit
Irms rated making capacity	15000 A at 1000 V AC for power circuit conforming to IEC 60158-1 15000 A at 1000 V AC for power circuit conforming to IEC 60947-4
Rated breaking capacity	12000 A at 500 V for power circuit conforming to IEC 60158-1 12000 A at 500 V for power circuit conforming to IEC 60947-4 15000 A at 440 V for power circuit conforming to IEC 60158-1 15000 A at 440 V for power circuit conforming to IEC 60947-4 5000 A at 1000 V for power circuit conforming to IEC 60158-1 5000 A at 1000 V for power circuit conforming to IEC 60947-4 9000 A at 660...690 V for power circuit conforming to IEC 60158-1 9000 A at 660...690 V for power circuit conforming to IEC 60947-4

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Associated fuse rating	1600 A aM at <= 440 V for power circuit 2000 A gI at <= 440 V for power circuit
Average impedance	0.13 mOhm - Ith 2000 A 50 Hz for power circuit
Power dissipation per pole	520 W AC-1 - Ith 2000 A
Inrush power in VA	1000 VA
Hold-in power consumption in VA	20 VA
Operating time	100...150 ms closing 20...40 ms opening
Mechanical durability	1200000 cycles
Maximum operating rate	120 cyc/h 55 °C
Rated operational power in VA	2000 VA at 110...127 V AC-1 - electrical durability: 1000000 cycles - for control circuit 3500 VA at 500 V AC-1 - electrical durability: 1000000 cycles - for control circuit 4000 VA at 220 V AC-1 - electrical durability: 1000000 cycles - for control circuit 4000 VA at 380 V AC-1 - electrical durability: 1000000 cycles - for control circuit 4000 VA at 415...440 V AC-1 - electrical durability: 1000000 cycles - for control circuit
Rated operational power in W	200 W at 500 V AC - electrical durability: 1000000 cycles - for control circuit 230 W at 440 V AC - electrical durability: 1000000 cycles - for control circuit 250 W at 110 V AC - electrical durability: 1000000 cycles - for control circuit 250 W at 220 V AC - electrical durability: 1000000 cycles - for control circuit
Height	500 mm
Width	475 mm
Depth	570 mm
Net weight	65 kg

Environment

Standards	VDE 0660 IEC 60158-1 NF C 63-110 IEC 60947-4 BS 5424
Product certifications	RINA CSA BV
Protective treatment	TC TH
Ambient air temperature for operation	-5...55 °C
Ambient air temperature for storage	-60...80 °C
Operating altitude	3000 m without derating

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	52 cm
Package 1 Width	58 cm
Package 1 Length	67 cm
Package 1 Weight	72.5 kg



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins