


Product data sheet

Specifications



servo motor SH3 055
1,05Nm,nokey,multi,brake,str.conn,I
P65/IP65,9k RPM

SH30553P02F1100

⚠ Discontinued on: Jun 30, 2023

⚠ Discontinued

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range Compatibility	PacDrive 3
Device short name	SH3
Product or Component Type	Servo motor

Complementary

Maximum mechanical speed	9000 rpm
[Us] rated supply voltage	115...480 V
Phase	Three phase
Continuous stall current	1.7 A
Continuous stall torque	9.29 lbf.in (1.05 N.m) 115...480 V three phase
Continuous power	680 W
Peak stall torque	31.0 lbf.in (3.5 N.m) 115...480 V three phase
Nominal output power	240 W 115 V single phase 460 W 230 V single phase 880 W 400 V three phase 970 W 480 V three phase
Nominal torque	10.001 lbf.in (1.13 N.m) 115 V single phase 9.7 lbf.in (1.1 N.m) 230 V single phase 7.17 lbf.in (0.81 N.m) 400 V three phase 7.17 lbf.in (0.81 N.m) 480 V three phase
Nominal speed	2000 rpm 115 V single phase 4000 rpm 230 V single phase 6000 rpm 400 V three phase 6000 rpm 480 V three phase
Maximum current Irms	6.5 A
Shaft end	Smooth shaft
Shaft diameter	0.4 in (9 mm)
Shaft length	0.8 in (20 mm)
IP degree of protection	IP65 motor: conforming to IEC 60034-5 IP65 shaft bushing: conforming to IEC 60034-5
Encoder type	Absolute multiturn SinCos Hiperface
Speed feedback resolution	128 periods
Holding brake	With
Holding torque	7.08 lbf.in (0.8 N.m)
Mounting Support	International standard flange

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Motor flange size	2.2 in (55 mm)
Electrical Connection	Straight connector
Torque constant	0.62 N.m/A 248 °F (120 °C)
Back emf constant	41 V/krpm 68 °F (20 °C)
Number of motor poles	3
Rotor inertia	0.155 kg.cm²
Stator resistance	10.4 Ohm
Stator inductance	37.98 mH
Maximum radial force Fr	190 N 8000 rpm 390 N 1000 rpm 310 N 2000 rpm 270 N 3000 rpm 240 N 4000 rpm 230 N 5000 rpm 210 N 6000 rpm 200 N 7000 rpm
Maximum axial force Fa	40 N
Type of cooling	Natural convection
Length	8.0 in (203 mm)
Centring collar diameter	1.6 in (40 mm)
Centring collar depth	0.08 in (2 mm)
Number of mounting holes	4
Mounting holes diameter	0.2 in (5.5 mm)
Circle diameter of the mounting holes	2.5 in (63 mm)
Product Weight	4.2 lb(US) (1.9 kg)
Sizing reference	SH30553P
Network number of phases	3
Temperature copper hot	266 °F (130 °C)
Electrical connection	straight connector

Ordering and shipping details

Category	US1PC5218359
Discount Schedule	PC52
GTIN	3606481971319
Returnability	No
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	4.567 in (11.600 cm)
Package 1 Width	15.669 in (39.800 cm)
Package 1 Length	7.677 in (19.500 cm)
Package weight(Lbs)	3.960 lb(US) (1.796 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Circularity Profile	No need of specific recycling operations