

# Product data sheet

Specifications

SQUARE D



## Two Speed Manual Switch - Flush - 2P - Toggle Operated - Red Indicator - 600VAC

2512KF11B

! Discontinued

### Main

|         |                           |
|---------|---------------------------|
| Product | Duplex Unit Manual Switch |
| Type    | K                         |

### Complementary

|                        |  |
|------------------------|--|
| Current Rating         | 30 A   |
| Horsepower Rating      | 2 hp 115 V AC<br>2 hp 230 V AC<br>3 hp 460 V AC<br>3 hp 575 V AC<br>1 hp 90 V DC<br>2 hp 115 V DC<br>1.5 hp 230 V DC |
| Maximum Voltage Rating | 600 V AC<br>230 V DC   |
| Number of Poles        | 2P   |
| Control Unit Type      | Toggle   |
| Number of Phases       | 1 phase  |
| Pilot Light            | Red indicator, 230 V   |
| Starter Type           | 2 speed  |
| Electrical Connection  | Screw clamp terminals  |
| Wire Gauge             | AWG 14...AWG 10 copper   |
| Height                 | 5.25 in (133.35 mm)  |
| Width                  | 5.25 in (133.35 mm)  |
| Depth                  | 2.19 in (55.63 mm)   |

### Environment

|                       |   |
|-----------------------|---|
| Certifications        | UL listed file E42243 CCN NLRV<br>CSA LR25490 class 3211 05 |
| NEMA Enclosure Rating | Not rated (flush plate) painted sheet steel standard size   |

### Ordering and shipping details

|                   |                        |
|-------------------|------------------------|
| Category          | 21102-2510,2511,2512 K |
| Discount Schedule | CP1                    |
| Returnability     | No                     |
| Country of origin | MX                     |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

# Packing Units

---

|                        |                       |
|------------------------|-----------------------|
| Unit Type of Package 1 | PCE                   |
| Nbr. of units in pkg.  | 1                     |
| Package weight(Lbs)    | 28.800 oz (816.466 g) |

---



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Longer



#### Lifetime extension

Repair

No