

Product datasheet

Specifications



Voltage release MSU 275VAac dc

A9N26979

⚠ Discontinued on: 9 Sept 2019

⚠ End-of-service on: 29 Apr 2019

⚠ Discontinued

Main

range of product	Librio Prodis Acti9 Clario
Product or component type	Overvoltage release
Device short name	MSU
[Uc] control circuit voltage	230 V AC 50 Hz
Threshold tripping voltage	275 V
9 mm pitches	2

Complementary

Range compatibility	Acti9 iDPN Acti9 C120 Acti9 C40 Acti9 C60H-DC Acti9 C60NA-DC Acti9 C60PV-DC Acti9 DPN Vigi Acti9 DT40 Acti9 DT60 Acti9 ID C40 Acti9 IDc Acti9 ITG40 Acti9 ID Acti9 DPN
Local signalling	Action indicator
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Height	82.5 mm
Width	18 mm
Depth	68 mm
Colour	White
Connections - terminals	Clamp terminal - 1 cable(s) 2.5 mm ² - flexible
Wire stripping length	9 mm
Tightening torque	1 N.m

Environment

Standards	EN/IEC 60947-5-1
-----------	------------------

Product certifications	ASTA KEMA ASEFA LCIE
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.8 cm
Package 1 Width	8 cm
Package 1 Length	9.5 cm
Package 1 Weight	0.077 kg

Contractual warranty

Warranty (in months)	18
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins