


Product datasheet

Specifications



BEH18 servo motor, Lexium 18, 380V,4.0kW,L130,17bit MAG MT

BEH18LM4033MA6D

Main

Range	Lexium 18
Range compatibility	Easy Lexium 18
Device short name	BEH18
Product or component type	Servo motor

Complementary

Maximum mechanical speed	3000 rpm
[Us] rated supply voltage	380 V
Network number of phases	Three phase
Continuous stall current	12.96 A
Continuous stall torque	12.6 N.m, 380 V, three phase
Continuous power	4000 W
Peak stall torque	37.8 N.m, 380 V, three phase
Nominal output power	4000 W, 380 V, three phase
Nominal torque	12.6 N.m, 380 V, three phase
Nominal speed	3000 rpm, 380 V, three phase
Maximum current Irms	38.88 A at 4 kW, 380 V
Maximum permanent current	38.88 A
Product compatibility	Motion servo drive motion servo motors motor at 4 kW, 380 V, three phase
Shaft end	Parallel key
Second shaft	Without second shaft end
Shaft diameter	28 mm
Shaft length	63 mm
Key width	8 mm
Feedback type	17 bits magnetic multi turn encoder
Speed feedback resolution	131072 points/turn
Holding brake	Without
Mounting support	Asian standard flange
Motor flange size	130 mm
Electrical connection	2 connectors male/female
Torque constant	0.9722 N.m/A at 40 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Back emf constant	67.87 V/krpm at 40 °C
Number of motor poles	10
Rotor inertia	10.1 kg.cm²
Maximum radial force Fr	686 N
Maximum axial force Fa	196 N
Type of cooling	Air-cooled
Length	230.9 mm
Number of mounting holes	4
Mounting holes diameter	9 mm
Width	130 mm
Height	174.5 mm
Depth	230.9 mm
Product weight	13 kg
Encoder type	Magnetic encoder
Inertia	10.1 kg.cm²

Environment

IP degree of protection	IP67
Ambient air temperature for operation	0...40 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25 cm
Package 1 Width	40 cm
Package 1 Length	60 cm
Package 1 Weight	15 kg
Unit Type of Package 2	P06
Number of Units in Package 2	6
Package 2 Height	90 cm
Package 2 Width	60 cm
Package 2 Length	80 cm
Package 2 Weight	96 kg

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Total lifecycle Carbon footprint	12 689 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	108 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	3 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	12 549 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	27 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better

 Materials and Substances	
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer

 Lifetime extension	
Repair	No

Use Again

 Repack and remanufacture	
Recyclability potential, in %	90
End of life manual availability	End of Life Information
Take-back	No