

Product datasheet

Specifications



auxiliary contact - 1 OC + 1 SD/OC - 380..415 V - 6 A

26929

⚠ Discontinued on: 30 Jun 2021

⚠ Discontinued

Main

range of product	Multi9
Product or component type	Double OC or fault contact
Device short name	OF and OF or OF and SD
Signal contacts composition	2 C/O
[In] rated current	DC-12 1 A at 130 V, DC DC-12 2 A at 48 V, DC DC-12 6 A at 24 V, DC AC-12 3 A at 415 V, AC 50/60 Hz AC-12 6 A at 240 V, AC 50/60 Hz
9 mm pitches	1
Standards	EN/IEC 60947-5-1
Product certifications	LCIE ASEFA KEMA ASTA

Complementary

Range compatibility	Multi9 C60 Multi9 C60CTRL Acti9 DPN Vigi Acti9 RCCB-ID 125A Acti9 iSW-NA
Mounting mode	Fixed
Mounting support	DIN rail
Height	84 mm
Width	9 mm
Depth	73 mm
Connections - terminals	Clamp terminal2 cable(s) 1.5 mm ² - flexible Clamp terminal2 cable(s) 1.5 mm ² - rigid Clamp terminal1 cable(s) 0.5...2.5 mm ² - flexible Clamp terminal1 cable(s) 0.5...2.5 mm ² - rigid
Wire stripping length	9 mm
Tightening torque	1 N.m

Environment

IP degree of protection	IP20 conforming to EN/IEC 60947-5-1
Pollution degree	3 conforming to EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.2 cm
Package 1 Width	8 cm
Package 1 Length	9 cm
Package 1 Weight	46 g

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

Yes

EU RoHS Directive

[Compliant](#)

Halogen-free status

Product contains halogen above thresholds

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

End of life manual availability

[End of Life Information](#)

Take-back

No

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins