

Product datasheet

Specifications



auxiliary blown fuse signalling contact - TeSys GS - 1st C/O - 3 poles - 630 A

GS1AF63

⚠ Discontinued

Main

Range of product	TeSys GS
Device short name	auxiliary blown fuse contact
Product or component type	Auxiliary contact
Product compatibility	GS 630
Poles description	3P
[Ie] rated operational current	12 A at 24 V DC-13 2 A at 48 V DC-13 3 A at 400 V AC-15 4 A at 230 V AC-15 0.4 A at 220 V DC-13 0.6 A at 110 V DC-13

Complementary

Fuse type	NFC DIN
Fuse size	T3
Contacts type and composition	1 NO/NC
Net weight	0.046 kg

Contractual warranty

Warranty (in months)	18
----------------------	----

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins