

SITRANS P DS III / P410, PROFIBUS PA, transmitter for pressure
***** Attention, product canceled / successor product
P320/P420 available! Please get in touch with your Siemens contact to determine
the successor product ***** Measuring cell filling silicone oil,
normal cleaning Nominal measuring range 16 bar g (232 psi g), overload limit 32
bar Diaphragm stainless steel, measuring cell stainless steel Process connection:
connection shank G1/2 B to EN 837-1 Die-cast aluminium housing Standard
design None explosion protection Electric connection and cable inlet: cable gland
M20 x 1.5 without visible digital indicator (digital display hidden, setting: mA)

Further information

Configurable Products

Technical Data and CAx data (3d-models , eplan.macros) from configurable products cannot shown here. To display the technical data for your device configuration please open PIA LifeCycleProtal and enter there your product number (MLFB). Exemplary 3d-models and eplan-macros are available at the industry imagadatabase. Data for a specific product can be requested with help of a support request.

PIA LifeCyclePortal

<https://pia-portal.automation.siemens.com>

Industry - Image Database

<http://www.automation.siemens.com/bilddb/>

Industry Mall (Online-Order System)

<https://mall.industry.siemens.com>

Information- and Downloadcenter (Catalogs, Brochures, ...)

<http://www.siemens.com/industrial-controls/catalogs>

Support Request

<https://support.industry.siemens.com/my/us/en/requests#createRequest>

last modified:

9/21/2024 