

Product datasheet

Specifications

Motors



AC servo motor BDH - 1.38 N.m -
8000 rpm - key shaft - without brake
- IP54

BDH0584C15A2A

⚠ Discontinued on: 8 Jul 2022

⚠ Discontinued

EAN Code: 3389118170940

Main

Product or component type	AC servo motors
Component name	BDH
Continuous stall torque	1.38 N.m for LXM15LU60N4 3 phases
Peak stall torque	3.94 N.m for LXM15LU60N4 at 230 V 3 phases 3.94 N.m for LXM15LU60N4 at 400 V 3 phases 3.94 N.m for LXM15LU60N4 at 480 V 3 phases
Nominal output power	270 W for LXM15LU60N4 at 230 V 3 phases 500 W for LXM15LU60N4 at 400 V 3 phases 600 W for LXM15LU60N4 at 480 V 3 phases
Nominal torque	1.13 N.m for LXM15LU60N4 at 480 V 3 phases 1.18 N.m for LXM15LU60N4 at 400 V 3 phases 1.28 N.m for LXM15LU60N4 at 230 V 3 phases
Nominal speed	2000 rpm for LXM15LU60N4 at 230 V 3 phases 4000 rpm for LXM15LU60N4 at 400 V 3 phases 5000 rpm for LXM15LU60N4 at 480 V 3 phases
Maximum mechanical speed	8000 rpm
Product compatibility	LXM15LU60N4 at 230 V 3 phases LXM15LU60N4 at 400 V 3 phases LXM15LU60N4 at 480 V 3 phases
Shaft end	Keyed
IP degree of protection	IP54
Encoder type	2-pole resolver
Speed feedback resolution	65536 points/turn
Holding brake	Without
Mounting support	International IEC standard flange
Electrical connection	Rotatable right-angled connectors
Number of poles	6

Complementary

Range compatibility	Lexium 15
Maximum current I _{rms}	4.03 A
Torque constant	0.97 N.m/A at 120 °C
Back emf constant	62.4 V/krpm at 120 °C
Stator resistance	20.4 Ohm at 20 °C
Stator inductance	43.8 mH at 20 °C

Stator electrical time constant	2.15 ms at 20 °C
--	------------------

Maximum radial force Fr	127 N at 8000 rpm 128 N at 7000 rpm 130 N at 6000 rpm 132 N at 5000 rpm 133 N at 4000 rpm 135 N at 3000 rpm 137 N at 2000 rpm 138 N at 1000 rpm
--------------------------------	--

Maximum axial force Fa	0.3 x Fr
-------------------------------	----------

Net weight	1.66 kg
-------------------	---------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No