

Product data sheet

Specifications



TeSys GS - switch-disconnector-fuse - 3 P - UL 400 A - fuse size J

GS2QU3

⚠ Discontinued

Main

Range	TeSys
Product name	TeSys GS
Device short name	GS2Q
Product or Component Type	Switch-disconnector-fuse
Poles description	3P
Protected poles description	3t
Contacts type and composition	3 NO
[Ith] conventional free air thermal current	400 A (at 104 °F (40 °C))
[Ie] rated operational current	250 A 690 V AC-23A 400 A 400 V AC-23A 400 A 400 V AC-22A 400 A 690 V AC-22A
Fuse type	UL
Fuse size	J
Network type	DC AC
Network Frequency	50/60 Hz

Complementary

Type of operating handle	External frontal
Mounting Support	Plate
[Uimp] rated impulse withstand voltage	8 kV
Short-circuit withstand	36 kA
Connections - terminals	Power circuit lugs-ring terminals 0.02...0.5 in ² (13.3...304 mm ²)

Environment

Standards	UL98 CSA C22.2 No 4
IP degree of protection	IP20 IEC 60529 with terminal cover)
Ambient Air Temperature for Operation	-4...158 °F (-20...70 °C)
Ambient Air Temperature for Storage	-40...176 °F (-40...80 °C)
Fire resistance	1760 °F (960 °C) body
Height	9.4 in (240 mm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Width	10.2 in (259 mm)
Depth	7.09 in (180 mm)
Net Weight	11.9 lb(US) (5.4 kg)

Ordering and shipping details

Category	22640-IEC DISCONNECT-GS1,LK3
Discount Schedule	I11
GTIN	3389119411431
Returnability	No
Country of origin	FR

Contractual warranty

Warranty (in months)	18
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.