

# Product datasheet

Specifications



## switch Acti9 iSW - 3 poles - 125 A - 415V

A9S60392

⚠ Discontinued on: 30 Jun 2023

**Price: 5,566.57 ZAR**

⚠ Discontinued

### Main

Range	Acti9
Product name	Acti9 iSW
Product or component type	Switch disconnecter
Device short name	iSW
Device application	Isolation Control
Poles description	3P
Utilisation category	AC-22A conforming to EN 60947-3 AC-22A conforming to IEC 60947-3
Suitability for isolation	Yes conforming to EN 60947-3 Yes conforming to IEC 60947-3

### Complementary

[Ie] rated operational current	125 A at 415 V AC 50/60 Hz
[Ue] rated operational voltage	415 V AC 50/60 Hz
[Ui] rated insulation voltage	500 V AC 50/60 Hz conforming to IEC 60947-3
[Uimp] rated impulse withstand voltage	6 kV conforming to EN 60947-3 6 kV conforming to IEC 60947-3
Control type	Toggle
Local signalling	ON/OFF indication
Contact position indicator	Yes
Mounting mode	Fixed
Mounting support	DIN rail
Comb busbar and distribution block compatibility	Standard
9 mm pitches	6
Height	77 mm
Width	54 mm
Depth	70 mm
Colour	White
Mechanical durability	50000 cycles
Electrical durability	2500 cycles

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

<b>Connections - terminals</b>	Tunnel type terminals - <= 50 mm <sup>2</sup> - rigid Tunnel type terminals - <= 35 mm <sup>2</sup> - flexible Tunnel type terminals - <= 35 mm <sup>2</sup> - flexible with ferrule
<b>Wire stripping length</b>	9 mm
<b>tightening torque</b>	3.5 N.m

## Environment

<b>Standards</b>	IEC 60947-3
<b>IP degree of protection</b>	IP4
<b>Pollution degree</b>	3 conforming to IEC 60947-3
<b>Tropicalisation</b>	2
<b>Relative humidity</b>	95 % at 55 °C
<b>Ambient air temperature for operation</b>	-20...50 °C
<b>Ambient air temperature for storage</b>	-40...70 °C

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	7 cm
<b>Package 1 Width</b>	5.3 cm
<b>Package 1 Length</b>	8 cm
<b>Package 1 Weight</b>	234 g
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	4
<b>Package 2 Height</b>	8 cm
<b>Package 2 Width</b>	9.5 cm
<b>Package 2 Length</b>	23 cm
<b>Package 2 Weight</b>	1.006 kg
<b>Unit Type of Package 3</b>	S03
<b>Number of Units in Package 3</b>	48
<b>Package 3 Height</b>	30 cm
<b>Package 3 Width</b>	30 cm
<b>Package 3 Length</b>	40 cm
<b>Package 3 Weight</b>	12.559 kg

## Contractual warranty

<b>Warranty (in months)</b>	18
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

<a href="#">EU RoHS Directive</a>	Compliant
SCIP Number	E5f22bd9-8e0c-4771-b932-618a392a4c8b
REACH Regulation	<a href="#">REACH Declaration</a>
Halogen-free status	Product contains halogen above thresholds

### Use Longer




#### Lifetime extension

Repair	No
--------	----

### Use Again



#### Repack and remanufacture

Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins