


# Product data sheet

Specifications



## XF communicating closing voltage release - 277 V AC - for MTZ drawout

LV839251

⚠ Discontinued on: Dec 9, 2025

⚠ End-of-service on: Dec 31, 2025

⚠ Discontinued

### Main

|                           |                                                                                                                                        |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Device short name         | XF com                                                                                                                                 |
| Product or component type | Voltage release                                                                                                                        |
| Device application        | Control                                                                                                                                |
| Range compatibility       | Masterpact MasterPact MTZ2 circuit-breaker<br>Masterpact MasterPact MTZ3 circuit-breaker<br>Masterpact MasterPact MTZ1 circuit-breaker |
| Voltage release type      | Closing coil                                                                                                                           |

### Complementary

|                              |                                                                                                    |
|------------------------------|----------------------------------------------------------------------------------------------------|
| Control type                 | Communicating                                                                                      |
| Signalling function          | Electrical push-button activated<br>Ready to close or open<br>Coil powered<br>Error                |
| [Uc] control circuit voltage | 277 V AC 50/60 Hz                                                                                  |
| Threshold tripping voltage   | 0.85...1.1 Un                                                                                      |
| Supply holding power         | 4.5 W<br>4.5 VA                                                                                    |
| Mounting mode                | Drawout                                                                                            |
| Response time                | 55 ms +/- 10 % MasterPact MTZ1<br>70 ms +/- 10 % MasterPact MTZ2<br>80 ms +/- 10 % MasterPact MTZ3 |

### Packing Units

|                              |     |
|------------------------------|-----|
| Unit Type of Package 1       | PCE |
| Number of Units in Package 1 | 1   |

### Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

| Materials and Substances               |     |
|----------------------------------------|-----|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic   | No  |

### Use Longer

| Lifetime extension |    |
|--------------------|----|
| Repair             | No |

### Use Again

| Repack and remanufacture |     |
|--------------------------|-----|
| Take-back                | Nej |